



MODIFICATION DESCRIPTION

SHEET

OF

1

-513

MOD

THIS MODIFICATION APPLIES TO THE FOLLOWING LINES AND SIZES ONLY

LINE	DTK	TJ	SUB-MIN	DL	DBA & DL-DBA	DS & MDS	PDS	CTD CTJ	CTL CTM	65009	CTR	CTA CTG	CTH CTN	DMS308 (P ONLY)
CONN. SIZE	8 /24	A L	ALL RECT. CYL.	A L	A L	A L L	A L L	A L L	A L L	A L L	A L L	A L L	A L L	A L L

-513 INSERT (MATERIAL)

Applies to all connectors listed above.

To be supplied with all applicable resilient parts made of MS 55 silicone elastomer.

SPECIAL APPLICATION

"0" ring on single hole mtg. receptacle shall be made of silicone elastomer (std)

RELEASE DATE 11-11-82

SUPERSEDES 4-1-82

APPROVED

LK PROJ. ENG. EW TEC. SEV. E. OF ENGS

THE DEUTSCH COMPANY

77-862 NOP

NOTICE-USED ON MIL SPEC QPL AND/OR CUSTOMER CONTROLLED PRODUCT(S): Approved Source Policies (TEC-1005) and/or Customer Change Requirements may apply. Receipt of this document does not constitute an approval.