

	Ξ		A					
		i						
					4			
AS EXA	AMPLE				3			
s whic er of t	non-conformit th does not co the Parties or b on, technical n	mply with by a third part	у					
untry	Jurisd	liction & Cont	rol List]	2			
^{=R} 3K3	Not Listed 35BN							
		CUSTOMER	R DRAWING	MOD N°				
Steel Receptacle 8D series								
ar	NPRDS / PROJECT 859							
J.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission								
	DRG N° 5BN-C			SHEET				
N.S.	B BIN-C		A	-, -	J			

					1	
	I	G	г	m		0
	Co	ntact Layout				Panel cutout
4						JAM NUT RECEPTACLE (TYPE 7)
	Contact position Location ID (mm) (mm) 1 428 (10.87) +.241 (10.97) 2 467 (11.86) +.154 (10.97) 3 488 (12.40) +.061 (10.96) 4 415 (11.64) +.011 (10.96) 5 488 (12.40) 061 (10.97) 7 428 (10.87) 142 (10.87) 7 428 (10.87) 237 (10.97) 8 332 (8.43) +.238 (10.87) 9 332 (8.43) +.238 (10.87)	m) position D (mm) (mm) (6.12) 51 +.000 (0.00) 047 (11) (3.91) 52 +.000 (0.00) 247 (6.02) (1.55) 53 +.000 (0.00) 237 (6.02) (0.01) 54 +.000 (0.00) 237 (6.02) (1.55) 55 +.000 (0.00) 247 (10) (3.61) 56 +.083 (2.11) +.475 (122) (6.02) 57 +.083 (2.11) +.380 (9.66) (8.46) 58 +.083 (2.11) +.285 (7.24)	1) 2) 30 35) 35) 5) 5)			ØC
ω	10 - 332 (8.43) + 143 11 - 332 (8.43) + 048 12 - 332 (8.43) - 047 13 - 332 (8.43) - 147 14 - 332 (8.43) - 147 15 - 332 (8.43) - 237 16 - 249 (6.32) + 380 17 - 249 (6.32) + 285 18 - 249 (6.32) + 190 (ns	3.63 60 +.083 (2.11) +.095 (2.41) (1.22) 61 +.083 (2.11) +.009 (0.00 (1.19) 62 +.083 (2.11) 005 (2.41) (3.61) 63 +.083 (2.11) 085 (2.41) (6.02) 64 +.003 (2.11) 286 (7.24) (8.43) 65 +.083 (2.11) 380 (9.65) (9.65) 66 +.083 (2.11) 380 (9.65) (7.24) 67 +.166 (4.22) +.478 (10.5)	1) 2) 1) 3) 4) 5) 577 777		E	Dim Nominal B 40.26+0/-0.25 ØC 41.53+0.25/-0
	Doosition ID X-axis (mm) Y-a (mm) 19 -249 (6.32) +.095 20 -249 (6.32) +.000 21 -249 (6.32) 955 22 -249 (6.32) 955 23 249 (6.32) 285	Design (2.41) Contact position ID position ID (mm) X-axis (mm) Y-axis (mm) (2.41) 69 +.166 (4.22) +.238 (6.0) (m0) (0.00) 70 +.166 (4.22) +.238 (6.0) (1.43) (2.41) (2.41) 71 +.166 (4.22) 048 (1.2) (1.43) (2.41) (1.43) (1.43) (2.41) (1.43) (1.43) (2.41) (1.43) (1.46) (1.42) 048 (1.2) (1.47) (1.46) (1.42) 048 (1.2) (1.47) (1.46) (1.42) 042 (1.42) (1.47) (1.46) (1.42) 042 (1.42) (1.47) (1.46) (1.47) (1.46) (1.42) 237 (0.0) (1.66) (1.22) 332 (8.4) (8.46) (76) +.166 (4.22) 427 (10) (1.42) 332 (8.4) (3.64)<	3) 2) 9) 1) 2) 2) 3) 85)			
	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	4) 3) 1) 0) 1) 3) 4) 5) 6) 5) 5) 5)			SOURIAU shall not be liable for any due to a use of the Products whi the Specifications issued by either of (professional recommendation) Country
N	42 083 (2.11) 190 43 083 (2.11) 285 44 063 (2.11) 380 45 083 (2.11) 375 46 +.000 (0.00) +.428	(0.00) 90 +332 (8.43) 047 (11) (2.41) 91 +332 (8.43) 142 (3.6) (4.83) 92 +.332 (8.43) 237 (6.0) (7.24) 93 +.332 (8.43) 332 (7.0) (9.65) 94 +.428 (10.87) +.241 (6.1) (12.07) 95 +.467 (11.86) +.154 (3.9) (10.87) 96 +.488 (12.40) +.061 (1.5) Contacts Sert arrangement 23-35)	9) 1) 2) 3) 2) 1)			PN: 8D723K
_	ID (mm) (n 47 +.000 (0.00) +.333 48 +.000 (0.00) +.238 49 +.000 (0.00) +.143 50 +.000 (0.00) +.048	Location Location mn) (mm) (mm) (mm) (8.46) 97 +415 (10.54) +000 (0.00) (6.05) 98 +488 (12.40) 061 (1.55) (3.63) 99 +428 (10.67) 142 (3.61) (1.22) 100 +.428 (10.87) 237 (6.02)	_		A 30-09-2010 ISS DATE Designed By:	6 First Release Latest modification - by Date:
	Shell Arrangement Number of size no. contacts 23 -35 100	f Size Service Contact Superse contacts rating location			SCALE	Stainless Ste
-					NA	Tolerances:
					FORMAT	WWW.SOURIAU.CO
					A3	8D723K3
	H	G	F	E	D	C

