



⑩	Metal	1	Metal plate for USB 120*18.5mm
⊕	Screw	4	Screw #4-40 2.8x14.7mm
⊗	Nut	4	Nut #4-40 4.75x2.0mm
⑦	Tube	4	Heat shrink Tube
⑥	Out molding	NA	PVC 45P Beige
⑤	Inner mold	NA	LDPE
④	Terminal	10	Pitch:2.54mm G/F
③	Housing	2	Pitch:2.54mm 5P Housing Black
②	CONN	2	USB A Female Shell:Nickel Pin:G/F Insulator color: White
①	Cable	2	USB2.0 UL2725 28#/1P+24#/2C+AEB OD:4.7mm Beige
NO.	NAME.	QTY	SPECIFICATION

Cable BLACK print
 AWM STYLE 2725 80°C 30V VW-1 28AWG/1P 24AWG/2C
 ---c AWM I/II A 80°C 30V FT1 USB CABLE

Electrical test:
 1. 100% short, open, miss wire test
 2. Conduct resistance: 2 Ohm max.
 3. Insulator resistance: 5Mohm min.
 4. Dielectric test: DC 300V

PIN ASSIGNMENT

P1		P2	
1	Red	1	Red
2	White	2	White
3	Green	3	Green
4	Black	4	Black
Shell	Drain	Shell	Drain

RoHS compliant
 Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	07.07.2016	Amy
						Approved	29.05.2018	Winnie
		②	Update the dimension	29.05.2018	Winnie			ASSMANN WSW-No.
		①	add the dimension of over molding	04.08.2017	Winnie			AK674
		⑩	Drawn	07.07.2016	Amy			Drawing-No.
								ASS 7689 CA
Angle	TOL	Id.	Modification	Date	Name			rev02
								Replace



ASS 7689 CA rev02