



NOTES:
1. CAPTURED CENTER CONTACT

RECOMMENDED MOUNTING HOLE

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	3/10/89	<i>YDD</i>

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER MIL-P-19468 AND FED SPEC L-P-403	N/A
CENTER CONTACT	BERYLLIUM COPPER PER QQ-C-530, ALLOY 173	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
CONTACT EXT. BUSHING	IRON-NICKEL ALLOY PER MIL-I-23011 CLASS 1 (KOVAR)	GOLD PLATE PER MIL-G-45204
METAL GASKET	SAE C12L14 STEEL ZZ-R-765	SILVER PLATE PER QQ-S-365
GLASS PERFORM	GLASS BEAD	N/A
COMPONENT	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. DEC. ANGLES
± 1/64 ± .005 ± °

DRAWN BY E.F. HOYLE DATE 3/8/89
CHECKED BY C. WARD 3/9/89
APPRD BY *YDD* 3/10/89

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASS'Y PROCEDURE

NO. AP. N/A

TITLE OSM PANEL FEEDTHROUGH JACK RECEPTACLE COMPRESSION SEAL WITH GASKET

SIZE B	CODE IDENT NO. 26805	2058-3289-00	REV 01 ₀
SCALE 5:1		SHEET 1 OF 1	