

APPLICABLE STANDARD																																												
RATING	OPERATING TEMPERATURE RANGE	-35°C TO 85°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO 60°C																																								
	VOLTAGE	30V AC	APPLICABLE CONNECTOR	DF37*-*DP-0.4V (**)																																								
	CURRENT	0.3A																																										
<b>SPECIFICATIONS</b>																																												
ITEM	TEST METHOD	REQUIREMENTS	QT	AT																																								
<b>CONSTRUCTION</b>																																												
GENERAL EXAMINATION	CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X																																								
MARKING	CONFIRMED VISUALLY.		X	X																																								
<b>ELECTRIC CHARACTERISTICS</b>																																												
CONTACT RESISTANCE	20mV AC OR LESS 1kHz, 1mA.	100mΩ MAX.	X	—																																								
INSULATION RESISTANCE	100V DC.	50MΩ MIN.	X	—																																								
VOLTAGE PROOF	100V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—																																								
<b>MECHANICAL CHARACTERISTICS</b>																																												
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	⚠	<table border="1"> <thead> <tr> <th rowspan="2">PIN COUNTS</th> <th>INSERTION FORCE</th> <th>WITHDRAWAL FORCE</th> </tr> <tr> <th>(N MAX)</th> <th>(N MIN)</th> </tr> </thead> <tbody> <tr><td>10</td><td>15.4</td><td>2.6</td></tr> <tr><td>16</td><td>20.7</td><td>3.6</td></tr> <tr><td>20</td><td>24.3</td><td>4.4</td></tr> <tr><td>24</td><td>27.8</td><td>5.1</td></tr> <tr><td>30</td><td>33.1</td><td>6.2</td></tr> <tr><td>34</td><td>40.8</td><td>6.9</td></tr> <tr><td>40</td><td>41.9</td><td>8</td></tr> <tr><td>50</td><td>50.7</td><td>9.8</td></tr> <tr><td>60</td><td>59.5</td><td>11.7</td></tr> <tr><td>70</td><td>68.4</td><td>13.5</td></tr> <tr><td>74</td><td>71.9</td><td>14.2</td></tr> </tbody> </table>		PIN COUNTS	INSERTION FORCE	WITHDRAWAL FORCE	(N MAX)	(N MIN)	10	15.4	2.6	16	20.7	3.6	20	24.3	4.4	24	27.8	5.1	30	33.1	6.2	34	40.8	6.9	40	41.9	8	50	50.7	9.8	60	59.5	11.7	70	68.4	13.5	74	71.9	14.2	X	—
			PIN COUNTS	INSERTION FORCE		WITHDRAWAL FORCE																																						
				(N MAX)	(N MIN)																																							
			10	15.4	2.6																																							
			16	20.7	3.6																																							
			20	24.3	4.4																																							
			24	27.8	5.1																																							
			30	33.1	6.2																																							
			34	40.8	6.9																																							
			40	41.9	8																																							
50	50.7	9.8																																										
60	59.5	11.7																																										
70	68.4	13.5																																										
74	71.9	14.2																																										
MECHANICAL OPERATION	10TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 10CYCLES, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
<b>ENVIRONMENTAL CHARACTERISTICS</b>																																												
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 85 °C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2 ~3 MIN)	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
SALT MIST	EXPOSED IN 5% SALT MIST FOR 48h.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																								
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																																								
⚠ 1	DIS-H-005746	KR. AJITO	TS. MIYAZAKI	11.05.16																																								
REMARKS		APPROVED	KH. IKEDA	10.02.08																																								
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT		CHECKED	TS. MIYAZAKI	10.02.08																																								
Unless otherwise specified, refer to JIS C 5402 and IEC 60512		DESIGNED	RT. SHIMIZU	10.02.08																																								
		DRAWN	RT. SHIMIZU	10.02.05																																								
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-329590-01																																									
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DF37SB-*DS-0.4V (51)																																									
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL684	⚠ 1/1																																								