



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATINGS: 30 mA @ 12VDC
5. CONTACTS: FIXED AND MOVING:  
COPPER ALLOY W/GOLD PLATE
6. CONTINUOUS CURRENT RATING 120mA
7. POWER RATING: 240mW
8. OPERATING FORCE: 150 ± 50 gf
9. OPERATING TRAVEL: 1.5MM ± 0.3MM
10. ▲ DENOTES CRITICAL PARAMETER.
11. 2002/95/EC (ROHS) COMPLIANT.

LED SPECS	UNITS	GREEN	GREEN
FORWARD CURRENT	mA	30 MAX	30 MAX
FORWARD VOLTAGE	V	1.9 - 2.8	1.9-2.8
LUMINOUS INTENSITY	mcd	15 TYP	15 TYP



TITLE 5511MBLKGRNGRN

A	20489	RELEASE FOR PRODUCTION	02/20/12	BMA
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
2:1	2/20/2012	BMA	XR0121P	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED