
KEMET Part Number: KJY471KR31DGAAA

(C803FR471K400CP)



KJY SFTY X1-400 Y2-250, Ceramic, Safety, 470 pF, 10%, 400 VAC (X1), 250 VAC (Y2), Y5P, Lead Spacing = 7.5mm



Dimensions		
D	8mm MAX	
Т	5mm MAX	
S	7.5mm MAX	
LL	25mm +/-1mm	
F	0.6mm +/-0.1mm	

Packaging Specifications	
Packaging:	Bulk, Bag

General Information		
Supplier:	KEMET	
Series:	KJY SFTY X1-400 Y2-250	
Style:	Radial Disc	
RoHS:	Yes	
Termination:	Tin	
Failure Rate:	N/A	
Qualifications:	ENEC, cUL, CQC, VDE	

Specifications		
Capacitance:	470 pF	
Capacitance Tolerance:	10%	
Voltage AC:	400 VAC (X1), 250 VAC (Y2)	
Dielectric Withstanding Voltage:	2,600 V	
Temperature Range:	-25/+85C	
Temperature Coefficient:	Y5P	
Dissipation Factor:	2.50%	
Insulation Resistance:	10 GOhms	
Safety Class:	X1/Y2	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

