


△	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	△	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△	1	RE-F-06478	J.M	md	99.7.29	△					
△						△					
<b>APPLICATION STANDARD</b>											
RATING	OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C			STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C			
	VOLTAGE		AC 50 V			OPERATING HUMIDITY RANGE		RELATIVE HUMIDITY 95% MAX (NO DEW CONDENSATION IS PERMITTED)			
	CURRENT		0.3 A								
<b>SPECIFICATIONS</b>											
ITEM		TEST METHOD				REQUIREMENT				QT	AT
<b>CONSTRUCTION</b>											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT				ACCORDING TO DRAWING				○	○
MARKING		CONFIRMED VISUALLY.								○	○
<b>ELECTRICAL CHARACTERISTICS</b>											
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).				60 mΩ MAX.				○	○
INSULATION RESISTANCE		100 V DC.				100 MΩ MIN.				○	—
VOLTAGE PROOF		150 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				○	○
<b>MECHANICAL CHARACTERISTICS</b>											
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE: 69.6 N MAX WITHDRAWAL FORCE: 2.9 N MIN				○	—
MECHANICAL OPERATION		50 TIMES INSERTION AND EXTRACTIONS.				1) CONTACT RESISTANCE: 70 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.				○	—
VIBRATION		FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE: 0.75 mm. — m/s <sup>2</sup> AT 10 CYCLES FOR 3 DIRECTIONS.				1) NO ELECTRICAL DISCONTINUITY OF 1 μs MIN 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.				○	—
SHOCK		490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.								○	—
<b>ENVIRONMENTAL CHARACTERISTICS</b>											
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90~95 %, 96 h				1) CONTACT RESISTANCE: 70 mΩ MAX. 2) INSULATION RESISTANCE: 100 MΩ MIN.				○	—
RAPID CHAGE OF TEMPERTURE		TEMPERTURE -55→15~35→ 85→15~35°C TIME 30→ 2~ 3→ 30→ 2~ 3 min. UNDER 5 CYCLES.				3) NO DAMAGE, CRACK AND LOOSENESS OF PART.				○	—
DRY HEAT		EXPOSED AT 85 °C, 96 h.				1) CONTACT RESISTANCE: 70 mΩ MAX.				○	—
COLD		EXPOSED AT -55 °C, 96 h.				2) NO DAMAGE, CRACK AND LOOSENESS OF PART.					
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				NO HEAVY CORROSION.				○	—
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JIS C 0090)				1) CONTACT RESISTANCE: 70 mΩ MAX. 2) NO HEAVY CORROSION.				○	—
RESISTANCE TO SOLDERING HEAT		REFLOW: RECOMMENDED TEMPERATURE PROFILE  25°C — 150°C — 160°C — 240°C — 200°C 60 S — 60~90 S — (30 S) — 120~30 S				NO MELTING OF RESIN WHICH AFFECTS THE PERFORMANCE OF COMPONENT.				○	—
SOLDRABILITY		SOLDERED AT SOLDER TEMPERATURE. 235 °C FOR IMMERSION DURATION, 2 s.				NO PINHOLE OR DEWETTING ON SOLDERED SURFACE				○	—
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
					S.Kitajima 99.05.25	J. Matsukawa 99.05.25	M.Ishida 99.05.26	Y.Yoshimura 99.05.27			
UNLESS OTERWISE SPECIFIED, REFER TO JIS C 5402.											
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST ○ APPLICABLE TEST											
<b>HRS</b> HIROSE ELECTRIC CO. LTD.		SPECIFICATION SHEET				PART NO FX11LB - 116P - SV					
CODE NO (OLD) CL		DRAWING NO ELC4 - 152106 -				CODE NO CL 573 - 0054 - 0				1	1

TO  
PCK

