

WXR3

3-Channel Power Unit, 420 W (600 W)
Product no.: WXR3N



Benefits

- › Up to three 200w high performance tools can be operated simultaneously for up to 600 watts of total power on the 3-channel, WXR3 rework system
- › Used for soldering and desoldering of both large and small SMT components
- › 2 internal pumps provide the sources for hot air, desoldering vacuum and a vacuum pick up tool for a completely self-contained rework system
- › LCD display simultaneously monitors all parameters, connected tools and peripheral devices.
- › Adjust parameter setting and other functions through menu
- › Compatible with all WX tools, accessories, and peripherals



For this purpose, we recommend:



Solder fume extractors



Soldering irons



Cleaning



Pre-heating plates



Technical Data

Dimensions L x W x H (mm)	273 x 235 x 102
Dimensions L x W x H (inches)	10,75 x 9,25 x 4,02
Weight (approx.) in kg	6.7
Voltage	120 V
Power	420 W (600 W)
Channels	3
Temperature range (depends on tool) °C	100 - 450 (550)
Temperature range (depends on tool) °F	200 - 850 (999)
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding socket	Via 3.5 mm pawl socket on back of device (Hard grounded)
Display	255 x 128 dots / Backlighting
Air consumption l/min	---
Operating pressure in bar/psi	---
Capacity l/min	18, max.
Vacuum	---

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE