

| | | | | |
|----------------------------|-----------------------------|---------------------------|---------------------------|-------------------------|
| APPLICABLE STANDARD | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -45°C TO +125°C (NOTES 1) | STORAGE TEMPERATURE RANGE | -10°C TO + 60°C (NOTE2) |
| | VOLTAGE | 150V AC | APPLICABLE CONNECTOR | DF9#-*P-1V (22) |
| | CURRENT | 0.5A | | DF9#-*P-1V (32) |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------|-------------|--------------|----|----|
|------|-------------|--------------|----|----|

CONSTRUCTION

| | | | | |
|---------------------|---------------------------------------|-----------------------|---|---|
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |


ELECTRIC CHARACTERISTICS

| | | | | |
|-----------------------|-------------------------|----------------------------|---|---|
| CONTACT RESISTANCE | 100m A (DC OR 1000 Hz). | 50mΩ MAX. | X | - |
| INSULATION RESISTANCE | 100V DC. | 500MΩ MIN. | X | - |
| VOLTAGE PROOF | 250V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | X | - |

MECHANICAL CHARACTERISTICS

| | | | | |
|----------------------|--|--|---|---|
| MECHANICAL OPERATION | 30TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: 50mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| SHOCK | 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |


ENVIRONMENTAL CHARACTERISTICS

| | | | | |
|---|---|--|---|---|
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -65 → 5 TO 35 → 125 → 5 TO 35°C TIME 30 → 10 TO 15 → 30 → 10 TO 15min UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | ① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| HEAT RESISTANCE OF SOLDERING | [RECOMMENDED TEMPERATURE PROFILE] 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 90~120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDELING CONDITION] SOLDERING IRON TEMPERATURE 380°C SOLDERING TIME : WITHIN 3 SECONDS. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | X | - |
| SOLDERABILITY | SOLDERING TEMPERATURE: 245 ± 5°C DURATION OF IMMERSION : SOLDERING FOR 3SECONDS | A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95% OF THE SURFACE BEING IMMersed. | X | - |
|  | | | | |

REMARKS


NOTE1: INCLUDING THE TEMPERATURE RISE BY CURRENT.
NOTE2: STORAGE IS DEFINED AS LONG-TERM STORAGE OF UNUSED PRODUCTS.
APPLY OPERATION TEMPERATURE RANGE TO PRODUCTS MOUNTED ON PCB WITHOUT POWER SUPPLY.

UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|--------------------------|---------------|--------------|----------|
|  1 | DIS-H-001204 | AR. TAKAHASHI | TS. MIYAZAKI | 06.08.02 |

| | | | |
|--|----------|--------------|----------|
| | APPROVED | TY. OMA | 04.03.31 |
| | CHECKED | TS. MIYAZAKI | 04.03.31 |
| | DESIGNED | HK. UMEHARA | 04.03.31 |
| | DRAWN | M. NAKAMOTO | 04.03.31 |

| | | | |
|------|--|-------------|----------------|
| Note | QT: Qualification Test AT: Assurance Test X: Applicable Test | DRAWING NO. | ELC4-162419-11 |
|------|--|-------------|----------------|

| | | | | |
|----------------------------|--|----------|----------------|---|
| SPECIFICATION SHEET | | PART NO. | DF9-*S-1V (32) | |
| HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL540 |  1/1 |