



- NOTES
- ① THE RECOMMENDED CLAMP TORQUE OF REF.NO. ⑥ TO BE 3 TO 3.5 N·m.
  - ② THE RECOMMENDED CLAMP TORQUE OF REF.NO. ⑩ TO BE 0.2 TO 0.25 N·m.  
 LOCTITE 243·HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ⑩ FROM LOOSENING.
  - 3 ROTATION EXAMPLES OF REF. NOS. ① AND ⑥ ARE SHOWN.
  - 4 THIS PRODUCT TO BE USED WITH CABLECLAMP, JR16WCC-\*.  
 \* DESIGNATE DIAMETER OF APPLICABLE CABLE.
  - 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,  
 DEPENDING ON THE CABLE STRUCTURE.  
 PLEASE CONFIRM BEFORE THE USE.

5	PHOSPHOR BRONZE	NICKEL PLATING	10	STAINLESS STEEL	HEX 1.27			
4	PHENOL-FORMALDEHYDE	(BLACK) UL94V-0	9	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
3	PHENOL-FORMALDEHYDE	(BLACK) UL94V-0	8	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)			
2	COPPER ALLOY	SILVER PLATING 2μm min.	7	BRASS	BLACK CHROME PLATING			
1	ALUMINUM ALLOY	BLACK CHROME PLATING	6	BRASS	BLACK CHROME PLATING			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS			
UNITS		SCALE	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
mm		2 : 1						
<b>HRS</b> HIROSE ELECTRIC CO., LTD.			APPROVED : HY. KOBAYASHI	18.02.26	DRAWING NO.	EDC-110570-31-00		
			CHECKED : HY. KOBAYASHI	18.02.26	PART NO.	JR16WP-7S(31)		
			DESIGNED : TH. KAMEYA	18.02.23	CODE NO.	CL114-2014-7-31		
			DRAWN : TH. KAMEYA	18.02.23				