



**DB25 AND XLR F AND XLR M WIRING CHART**

XLR (CHANNEL)	XLR (DESC.)	CABLE (COLOR)	PIN 2 (RED)	PIN 3 (BLACK)	PIN 1 (BARE)
1	XLRF	BROWN	24	12	25
2	XLRF	RED	10	23	11
3	XLRF	ORANGE	21	9	22
4	XLRF	YELLOW	7	20	8
5	XLRM	GREEN	18	6	19
6	XLRM	BLUE	4	17	5
7	XLRM	PURPLE	15	3	16
8	XLRM	GRAY	1	14	2

PART NUMBER	CABLE LENGTH "X"
DB25M02XLRMXMLRF	2.00 FT +/- 1.50 IN
DB25M10XLRMXMLRF	10.00 FT +/- 1.50 IN

- NOTES:
- BREAKOUT CABLE LENGTH: 18.00 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
  - THIS PRODUCT COMES COILED AND PACKAGED IN BAG.

3. JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (2) AND #M3 THREAD (2) JACKSCREWS.
4. MATERIALS:  
 XLR CONNECTORS:  
 HANDLE - ZINC ALLOY, NICKEL PLATED  
 HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED  
 INSULATOR - THERMOPLASTIC, GREEN  
 CONTACTS AND PINS - SPECIAL COPPER ALLOY, SILVER PLATED  
 H.S. TUBING - THERMOPLASTIC  
 DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS  
 JACKSCREWS - STAINLESS STEEL

5. THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

					UNLESS OTHERWISE SPECIFIED					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					1. ALL DIMENSIONS IN INCHES					SIZE	WIDTH	MULT	LBS/M	TEMPER
					- TWO PLACE DECIMALS ±0.02					FINISH		MATERIAL		
					- THREE PLACE DECIMALS ±0.005					SPEC No.		SPEC No.		
D	26795	7-8-11	TO	TJK						FIRST USED ON		SCALE		
C	26637	10/11/10	RS	TJK						DATE DRAWN		BY	CHKD	APVD
B	25891	9/9/08	SRC	TJK						9/12/06	JGK	RS	TJK	
A	25716	10/03/07	JGK	TJK								11/10/10	11/10/10	
REV	ECO NUMBER	DATE	BY	APVD						NAME		PART No.		
REVISIONS					DO NOT SCALE DRAWING					DB25M TO 4 XLRF & 4 XLRM, RoHS		DB25M__XLRMXMLRF		