



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to

IEC 60169-4, VG 95250, EN 122190, DIN 47223

**Documents**

Assembly instruction

53 03

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Body  
Dielectric  
Gasket  
Crimping ferrule

**Material**

Spring bronze  
Brass  
Brass  
PTFE  
Silicone  
Copper

**Plating**

Silver, 3-6  $\mu\text{m}$   
Flash white bronze over silver(e.g. Optargen®)  
Flash white bronze over silver(e.g. Optargen®)  
Flash white bronze over silver(e.g. Optargen®)

**Electrical data**

Impedance	50 $\Omega$
Frequency	DC to 7.5 GHz
Return loss	$\geq 35$ dB, DC to 2.5 GHz $\geq 28$ dB, 2.5 to 4 GHz
Insertion loss	$\leq 0.05$ dB
Insulation resistance	$\geq 10^4$ M $\Omega$
Center contact resistance	$\leq 0.4$ m $\Omega$
Outer contact resistance	$\leq 1.5$ m $\Omega$
Working voltage (at sea level)	500 V rms, 50 Hz
Power handling (at 20 °C, sea level, VSWR 1.0)	1800 W @ 1 GHz 800 W @ 4 GHz
RF-leakage	$\geq 128$ dB up to 1 GHz

- Limitations are possible due to the used cable type -

**Mechanical data**

Mating cycles	min. 500
Coupling nut retention	$\geq 1000$ N
Center contact captivation: axial	$\geq 200$ N
radial	$\geq 2$ Ncm
Coupling torque (recommended)	25 to 30 Nm
Proof torque	max. 35 Nm

**Environmental data**

Temperature range	-45°C to +85°C
Rapid change of temperature	DIN EN 122190, clause 4.6.7
Corrosion salt mist	DIN EN 122190, clause 4.6.10
Vibration	DIN EN 122190, clause 4.6.3
Damp heat	DIN EN 122190, clause 4.6.6
Climatic tests	DIN EN 122190, clause 4.6.5 (45/85/56)
RoHS	compliant

**Tooling**

Crimping tool	11W150-000
Crimp insert	11W150-215

**Suitable cables**

RG 213 /U

**Weight**

Weight	107.1 g/pce
--------	-------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	29/06/04	J_Gramsamer	01.04.15	f00	15-0397	J_Krautenb.	01.04.15
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2