



- THIS PART WILL ACCEPT NINE (9) MULTIMATE PIN CONTACTS.
- HOUSING AND PRESSURE PLATE: NYLON, BLACK.
 PERIPHERAL SEAL: ELASTOMER, GRAY.
 WIRE ENTRY SEAL: ELASTOMER, RED-IRON OXIDE.
 THREADED INSERTS: BRASS
- OBSELETE PARTS: OBSELETE CIS STREAMLINING PER D.RENAUD/D.SINISI

3	OBSELETE	YES	.040-.080	SMALL	788158-3
		NO	.065-.120	STANDARD	788158-2
3	OBSELETE	NO	.040-.080	SMALL	788158-1
		THREADED INSERTS	DIAMETER RANGE	INSULATION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN	26 AUG 98	TE Connectivity			
mm [INCHES]		CHK	26 AUG 98				
		APVD	26 AUG 98				
		NAME		RECEPTACLE ASSEMBLY, 13-9, STANDARD SEX, SERIES I, SEALED, CIRCULAR PLASTIC CONNECTOR			
		APPLICATION SPEC					
MATERIAL	FINISH	WEIGHT		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
				A2	00779	G-788158	
RESTRICTED CUSTOMER				SCALE	SHEET	REV	
				2:1	1 of 1	B2	