Product Configuration System

Crystal Oscillators - High Stability

HG-8002 | JA | 100.0000M | - | P | H | AV | L3 | : | PURE SN

Model Number

Package Type
JA: Plastic 14.0x9.8x4.7mm

Output Frequency Range
M: Units in MHz
1.0 ~ 125MHz / 5.0V Vdd / 3.3V Vdd
* Please see Frequency Tolerance

Function
P: OE
S: ST

Power Supply (Vdd) Duty Level
H: 5.0V, CMOS (50% Vdd)
T: 5.0V, TTL (1.4V)
C: 3.3V, CMOS (50% Vdd)

Packaging
Tape and Reel Qty
JA Package
Blank: Bulk
L0: 1000pcs per reel
L3: 250pcs per reel

DC Package
S: 35 pcs per Stick

*** Frequency Tolerance / Freq Range / Vdd Duty**
AV: +/-20ppm (-20˚ ~ +70˚C) 1~125MHz PH/PT/PC/SH/ST/SC
BV: +/-25ppm(-20˚ ~ +70˚C) 1~125 MHz PH/PT/PC/SH/ST/SC
CX: +/-30ppm (-40˚ ~ +85˚C) 1~55MHz PH/PT/SH/ST

PURE SN
ROHS
Blank = Not RoHs Compliant

EPSON TOYOCOM