



* COMPLETELY TIGHTENED

- NOTES:**
- MATERIALS:**
 HOOD: PBT GF UL94 V-0 BLACK
 FRONTSEALING: SILICONE VMQ BLUE
 SCREW: STAINLESS STEEL
 O-RING: NBR BLACK
 - TEMPERATURE RANGE: -30°C TO +90°C
 - RECOMMENDED TORQUE FOR SCREW:
 35Ncm (3.1 in.LB)
 MAX. TORQUE: 68Ncm (6 in.LB)
 - SINGLE PACKED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		±0,3 unless otherw. specified		dim. in mm	scale:	1,5:1 (1:1)			
						material:	SEE NOTES			
	drawn	07.02.2014	Heinrich		title:					
	appd.	07.02.2014	Huether		WATER RESISTANT D-SUB HOOD					
						25 POS.				
						SHORT SCREW 4-40UNC STAINLESS STEEL				
						dwg no:		15K1A1437		DIN-A3
						part no:		15-004730		
										sh: 1
	rev.	description	date	name						
a	Origin									