

## Specification Sheet

Part Number: MP3M3.NN3P



Cable Tie Mounting Plates, .50" x 4.25", T18-T50 Cable Ties, #6 (M3) Screw, PA66, Natural, 100/pk

<b>Article Number</b>	151-24319
<b>Type</b>	MP3M3
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Mounting plates allow multiple bundles to run parallel.</li><li>•The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Mounting Plates allow multiple cables to be run in parallel. Mounts are secured with two screws. Cables are attached to the plates by running a cable tie through any of the available slots.
<b>Short Description</b>	Cable Tie Mounting Plates, .50" x 4.25", T18-T50 Cable Ties, #6 (M3) Screw, PA66, Natural, 100/pk

**Global Part Name**

MP3M3-PA66-NA

**Length L (Imperial)**

4.25

**Length L (Metric)**

108.0

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.5

**Width W (Metric)**

12.7

**Cable Ties**

T18 - T50

**Height H (Imperial)**

0.125

**Height H (Metric)**

3.2

**Cable Tie Width Max (Imperial)**

0.2

**Cable Tie Width Max (Metric)**

5.2

**Mounting Hole Diameter D (Imperial)**

0.15

**Mounting Hole Diameter D (Metric)**

3.7 mm

**Mounting Hole Diameter D Max (Metric)**

3.7

**Mounting Hole Centers (Imperial)**

1.25

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	RATP   NF EN [45545-2]
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.