

## L6R12H Series

# 12W Wall Mount Power Supply

- DOE Level VI Efficiency Rating
- Universal Input: 90 ~ 264Vac, 47/63 Hz
- UL/cUL Safety Approved
- Corded Output Connection
- Light Weight and Compact



Model No.	Application	Output Connector	Output Voltage	Output Current			Voltage Accuracy	Ripple Noise	Line Reg.	Load Reg.
				Min	Rated	Peak				
L6R12H-050	ITE	2.1mm I.D. x 5.5mm O.D. x 9.5mm Barrel	+5.0V	0	2.1	—	±5%	< ± 1%	± 1%	± 5%
L6R12H-059	ITE		+5.9V	0	1.8	—	±5%	< ± 1%	± 1%	± 5%
L6R12H-070	ITE		+7.0V	0	1.7	—	±5%	< ± 1%	± 1%	± 5%
L6R12H-090	ITE		+9.0V	0	1.0	—	±5%	< ± 1%	± 1%	± 5%
L6R12H-120	ITE		+12.0V	0	1.0	—	±5%	< ± 1%	± 1%	± 5%

- Output voltages from 5.0Vdc to 12.0Vdc are available in increments of 0.1V. Please contact Tri-Mag, LLC for the part number and specifications for your output voltage requirement and application.
- The output voltage is verified to specs at 60 percent rated load condition.
- The **line regulation** is defined by changing ± 10 percent of input voltage from the nominal line at rated load.
- The **load regulation** is defined by changing ± 40 percent of the measured output load from 60 percent of the rated load.
- The **ripple and noise** is measured by using 20MHz bandwidth limited oscilloscope with each output terminated with a 10 µF electrolytic and a 0.1 µF capacitor at rated load and nominal line.
- The **efficiency** is measured at rated load and nominal line.

# L6R12H Series

Innovative, reliable, and inexpensive. That's the **L6R12H Series**.

This economical, DOE Level VI compliant power supply/charger is rated up to 12W when charging any mobile or wireless device.

Plenty of voltage levels to choose from, too. From 5.0Vdc to 12.0Vdc (in increments of 0.1V), to match your need.

Contact us (800-657-0853 or Sales@Tri-Mag.com) for the part number to match your specifications.

## Specifications

### Input

Input Voltage	• 90 Vac ~ 264 Vac
Input Frequency	• 47 Hz to 63 Hz
No Load Input Power	• < 0.1W
Input Current	• 1.2A Max.
Inrush Current	• 40A Max.
Leakage Current	• 0.25mA Max.
Input Connection	• US (others available)

### Output

Output Voltage Range	• 5.0 to 12.0 Vdc
Output Current Range	• 500 - 2100mA, 12W Max.
Minimum Load	• No min. load required.
Line Regulation	• ± 1% at rated load across input voltage range
Load Regulation	• ± 5%
Ripple & Noise	• 100mVp-p Max.
Overvoltage Protection	• Auto recovery
Overload Protection	• Auto recovery
Short Circuit Protection	• Auto recovery

### General

Insulation Resistance	• 50MΩ Min.
Efficiency	• Level VI compliant
MTBF	• 50,000 hrs to MIL-HDBK-217F at +25°C

### Environmental

Operating Temperature	• 10°C to 40°C
Operating Humidity	• 5% - 95% RH, Non-Condensing
Storage Temperature	• -20°C to +80°C

### EMC & Safety

Safety Approvals	• UL: UL60950-1 • cUL: UL60950-1
EMC Approvals	• FCC

### Warranty

Warranty Period	• 1 year
-----------------	----------

### Dimensions and Notes

Dimensions in mm	
Tolerance	• ± 0.2mm
Size	• 74.0 x 29.0 x 48.0 mm 2.91 x 1.14 x 1.89 Inches
Weight	• Approx. 120g (4.2 oz.)
Connectors	• AC input, US 2-prong inlet plug DC output, standard 2.1mm x 5.5mm x 9.5mm cored dc barrel connector or per customer specification.
Cord length	• 1500 ± 20 mm (59 ± .8")

### Mechanical Drawing

