


Cylinder Type PAS Capacitor(High Reliability type)[LN series]

PAS1220LN2R7905



■ Features

- Item Summary
9F, 2.7(2.3)V, phi 12.5x20.0mm
- Lifecycle Stage
Mass Production

■ Products characteristics table

| | |
|-------------------------------|--------------------------|
| Nominal Capacitance | 9 F |
| Max. Usable Voltage1 | 2.7 V (at -40 to +70 °C) |
| Max. Usable Voltage2 | 2.3 V (at -40 to +85 °C) |
| Initial Internal Resistance | 60 mΩ max |
| Initial Capacitance | 9 F ±20% |
| Operating Temp. Range1 | -40 to +70 °C |
| Operating Temp. Range2 | -40 to +85 °C |
| RoHS2 Compliance (10 subst.) | Yes |
| REACH Compliance (173 subst.) | Yes |
| Soldering | Wave |

■ External Dimensions

| | |
|-------------|------------------|
| Dimension D | phi 12.5 ±0.5 mm |
| Dimension L | 20.0 ±2.0 mm |
| Dimension d | Typ phi 0.6 mm |
| Dimension P | 5.0 ±0.5 mm |

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.