

THIS DRAWING IS A CONTROLLED DOCUMENT
RELEASED FOR PUBLICATION JULY, 1998
BY AMP INCORPORATED. ALL RIGHTS RESERVED.
COPYRIGHT 1998

AMP 1281 (7/83)

APPLICATOR PARTS LIST

TYPE
**RING
AMPLIVAR
STUD RETAINING**

**AMP INCORPORATED
HARRISBURG, PENNA.**

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER	1	456424-2	42	WIRE TRIMMER	1	811264-2	
2	INS. CRIMPER			43				
3	ANVIL	1	2-473405-0	44				
4	ANVIL SPACER			45				
5	SHEAR BLADE	1	2-465233-5	46				
6	REAR SHEAR PLATE	1	385013-4	47				
7	SHEAR BLADE SPACER	2	373072	48				
8	FRONT SHEAR PLATE	1	470857-3	49				
9	REAR ANVIL SPACER PLT.	1	386149	50				
10	FRONT ANVIL SPACER PLT.	1	385528	51				
11	TOOL SPACER	1	371355	52				
12	TOOLSPACER	1	371040	53	HOLD DOWN (BLADE MT.)	1	811065-1	
13	FRONT STRIP GUIDE	1	379034-1	54				
14	REAR STRIP GUIDE	1	379034-2	55				
15	RAM	1	471167	56				
16	TOOL HOLDER	1	376046	57				
17	ADJ. CRIMP MOUNT			58				
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT ASSY.	1	570656	60				
20	BASE PLATE			61				
21	BASE BLOCK			62				
22	STRIP GUIDE PLATE			63				
23	ANVIL HOLDER	1	370526	64	AIR FEED ASS'Y (2")	1	690021	
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ. PLATE	1	374999	
25	STRIPPER & WIRE TRIMMER	1	811265-1	MISCELLANEOUS				
26	STRIPPER MOUNT	2	386231	66	LUBRICATOR ASS'Y	1	465184-2	
27	RETAINER PLATE	2	372251	67	TERMINAL LUBRICANT	REF	852931-2	
28	STRIPPER MOUNT BRACKET			68	AIR BLAST ASS'Y	1	455350-1	
29	STRIPPER BUSHING			69	COPPER TUBING	1	689446-2	
30	STOCK DRAG	1	375381	70	ELBOW	1	22317-3	
31	STOCK DRAG HANDLE			71				
32	STOCK DRAG STUD	2	354045-1	72				
33	STOCK DRAG SPRING	2	1-23847-1	REV. REVISION RECORD				
34	STOCK DRAG ADJ. SCREW	2	372997	REV.	REVISION RECORD	DATE	BY	ECN
35	FEED FINGER HOLDER			F2	ECR-06-007163	3-06	MY TE	
36	FEED FINGER	1	375093	F1	ECR-06-004495	2-06	MY EG	
37	FEED FINGER TIP			F	0150-8939-98	11/98	MC MY	
38	FEED FINGER SPACER			E	ECN A-395892	9-92	MS TB	
39	BASE CASTING	1	570238	D	EC-A-272490	10-16-93	JZ CG	
40	GUARD	1	457664-7	C	REV PER ECN	12/6/83	WJ TR	5383
41	SPACER, GUARD	2	375570	B	REV PER ECN R	12-6-82	PS JG	4812
				A	REV PER ECN R	8-82	BB B	4657

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				505079
108-16000				1742334
WIRE SIZE		CRIMP HEIGHT		770392
(1) 19 3/4 + (1) 15 1/4		.062		
(1) 20 + (1) 15		.062		
(1) 24 + (1) 17 3/4		.053		
(1) 24 1/2 + (1) 19 3/4				.049
CRIMP	SIZE	TYPE	FEED	
WIRE	.130	F		
INSUL.	---	---	1.280	
SLEEVED	---	---		
INSULATION RANGE		WIRE RANGE		
---		MAG. WIRE		
EXPLODED VIEW				
A-6000 & A-6000-1				
REMARKS:				
TOP TOOL MTG. FROM				
RAM OUT 5, 11, 12, 42 & 1				
■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT				
THIS APPLICATOR IS TO BE USED ON				
AMP-O-LECTRIC 1-471273-2				DIST.
AMP-O-MATIC AIR FEED				4
AUGN-GA-679597-1				
SERIAL NO.		DATE SHIPPED		DESIGNED
				K. STAREM
				11/13/81
CUSTOMER NAME AND ADDRESS				CHK'D.
				1KM
				11/91
				APP'D.
				11CM
				11/91
APPLICATOR NUMBER	REV.	SHEET		
F2	566326-1	1 OF 1		