

| APPLICABLE STANDARD |                             |                 |                                     |  |
|---------------------|-----------------------------|-----------------|-------------------------------------|--|
| RATING              | OPERATING TEMPERATURE RANGE | -40 °C TO 85 °C | STORAGE TEMPERATURE RANGE           | -10 °C TO 50 °C (PACKED CONDITION)     |
|                     | VOLTAGE                     | 50 V AC / DC    | OPERATING OR STORAGE HUMIDITY RANGE | RELATIVE HUMIDITY 90 % MAX (NOT DEWED) |
|                     | CURRENT                     | 0.5 A (note 1)  | APPLICABLE CABLE                    | t=0.3±0.05mm, GOLD PLATING             |

### SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------|-------------|--------------|----|----|
|------|-------------|--------------|----|----|

#### CONSTRUCTION

|                     |                                       |                       |   |   |
|---------------------|---------------------------------------|-----------------------|---|---|
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING             | CONFIRMED VISUALLY.                   |                       | X | X |

#### ELECTRIC CHARACTERISTICS

|                       |                     |   |   |   |
|-----------------------|---------------------|---|---|---|
| CONTACT RESISTANCE    | 1mA(DC OR 1000Hz).  | 50 mΩ MAX.<br>INCLUDING FPC,FFC BULK RESISTANCE (L=8mm) | X | X |
| INSULATION RESISTANCE | 100 V DC.           | 500 MΩ MIN.   | X | X |
| VOLTAGE PROOF         | 150 V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN.                              | X | X |

#### MECHANICAL CHARACTERISTICS

|                      |   |  |   |   |
|----------------------|---|--|---|---|
| MECHANICAL OPERATION | 20 TIMES INSERTIONS AND EXTRACTIONS.  | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | — |
| VIBRATION            | FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75 mm, FOR 10 CYCLES IN 3 AXIAL DIRECTIONS.                   | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② CONTACT RESISTANCE: 50 mΩ MAX.     | X | — |
| SHOCK                | 981 m/s <sup>2</sup> , DURATION OF PULSE 6 ms AT 3 TIMES IN 3 BOTH AXIAL DIRECTIONS.                  | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.                                     | X | — |
| FPC RETENTION FORCE  | MEASURED BY APPLICABLE FPC. (CONNECTOR,FPC AT INITIAL CONDITION. THICKNESS OF FPC SHALL BE t=0.30mm ) | DIRECTION OF INSERTION: 0.4 × n N MIN (n:NUMBER OF CONTACTS)                   | X | — |

#### ENVIRONMENTAL CHARACTERISTICS

|                                |  |   |   |   |
|--------------------------------|--|---|---|---|
| RAPID CHANGE OF TEMPERATURE    | TEMPERATURE-40→+15To+35→+85→+15To+35°C<br>TIME 30→ 2 To 3 → 30→ 2 To 3 min.<br>UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② INSULATION RESISTANCE: 50 MΩ MIN.<br>③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.   | X | — |
| DAMP HEAT (STEADY STATE)       | EXPOSED AT 40±2 °C,<br>RELATIVE HUMIDITY 90 TO 95 %, 96 h.                                     |   | X | — |
| DAMP HEAT,CYCLIC               | EXPOSED AT -10 TO +65 °C,<br>RELATIVE HUMIDITY 90 TO 96 %, 10 CYCLES,TOTAL 240 h.              | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY)<br>③ INSULATION RESISTANCE: 50 MΩ MIN. (AT DRY)<br>④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | — |
| DRY HEAT                       | EXPOSED AT 85±2 °C, 96 h.  | ① CONTACT RESISTANCE: 50 mΩ MAX.  | X | — |
| COLD                           | EXPOSED AT -40±3°C, 96 h.  | ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  | X | — |
| CORROSION SALT MIST            | EXPOSED AT 35±2 °C 5% SALT WATER SPRAY FOR 96 h.   | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.   | X | — |
| SULPHUR DIOXIDE [JIS C 0090]   | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% , 25±5 PPM FOR 96 h.                              |   | X | — |
| HYDROGEN SULPHIDE [JIS C 0092] | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% , 10 TO 15 PPM FOR 96 h.                          |   | X | — |

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|-------|--------------------------|----------|---------|------|
| 0     |                          |          |         |      |

|        |          |                |          |
|--------|----------|----------------|----------|
| REMARK | APPROVED | NM. NISHIMATSU | 12.03.21 |
|        | CHECKED  | HS. SAKAMOTO   | 12.03.21 |
|        | DESIGNED | RT. IKEDA      | 12.03.20 |
|        | DRAWN    | NM. SANPEI     | 12.03.14 |

Unless otherwise specified, refer to JIS C 5402.

|  |             |                |
|--|-------------|----------------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | DRAWING NO. | ELC4-159266-02 |
|--|-------------|----------------|

|            |                           |          |                      |       |
|------------|---------------------------|----------|----------------------|-------|
| <b>HRS</b> | SPECIFICATION SHEET       | PART NO. | FH12-**S-0.5SVA (54) |       |
|            | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL586                | ▲ 1/2 |

| SPECIFICATIONS   |   |  |                        |    |     |
|--|---|--|------------------------|----|-----|
| ITEM   | TEST METHOD   | REQUIREMENTS   | QT                     | AT |     |
| RESISTANCE TO SOLDERING HEAT   | 1) REFLOW SOLDERING (TO BE 2 TIMES MAX.)<br>PEAK TMP. 250 °C MAX<br>REFLOW TMP. 230 °C MIN FOR 30 sec.<br>PRE-HEATING. 150 TO 200°C<br>90 TO 120 sec.<br>2)SOLDERING IRONS : 350 ± 10 °C,<br>FOR 5± 1 sec . | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.                              | X                      |    | —   |
| SOLDERABILITY  | SOLDERED AT SOLDER TEMPERATURE, 235±5 °C FOR IMMERSION DURATION, 2±0.5 sec.   | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED. | X                      |    | —   |
| <p><b>(note 1)</b></p> <p>WHEN THE SAME VALUE OF CURRENT ARE APPLIED TO ALL CONTACTS AT THE SAME TIME IN ONCE, SET THE CURRENT TO THE 70 % OF THE RATED CURRENT VALUE.</p> |   |  |                        |    |     |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test   |   | DRAWING NO.  | ELC4-159266-02         |    |     |
|  | SPECIFICATION SHEET   | PART NO.   | FH12-***S-0. 5SVA (54) |    |     |
|  | HIROSE ELECTRIC CO., LTD.   | CODE NO  | CL586                  |    | 2/2 |