

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

LOC
CMDIST
00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B1	REVISED PER ECO-12-015596	11OCT2012	RGV	DCS
	C	REVISED PER ECO-13-002574	13FEB2013	DLD	DCS

- TORQUE FAILURE TO BE 3.4 - 4.5 Nm [30 - 40 IN LB].
- CUMMINS ELECTRONICS MUST BE INFORMED BY WAY OF A PRODUCT CHANGE IDENTIFICATION OF ALL CHANGES TO THE TE CUSTOMER DRAWINGS.

3 NOTE DELETED.

7.00
6.85
HEX

SCREW

1.76
1.26

8.13

2.92
2.67

20.00

WASHER

M4 X 0.7-6g

8.46
8.20

212982-1

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
R. VESTAL 13AUG2012CHK
D. STRAUSSER 13AUG2012APVD
D. STRAUSSER 13AUG2012

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

-

Customer Drawing

STE

TE Connectivity

NAME

SCREW, HEX HEAD,
M4 X 0.7, ECMSC

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-212982

-

SCALE 5:1

SHEET 1 OF 1

REV C

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±0.13
4 PLC	±-
ANGLES	±-

MATERIAL

STAINLESS STEEL

FINISH

PASSIVATED

1470-19 (3/11)