| | D I | m rr | | C B | Þ | | |
|----------|--|--|--------------------------|------------------------------------|--|---|--|
| 4 | Z Description of the second s | ØF | | | | 4 | |
| ယ | | | | LAYOUT SHOWN AS EXAMPLE | | 3 | |
| | | Keying Shown as example | | | | | |
| | CHARACTERISTICS | Connector dimension | | | | | |
| | -Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer | DimNominalF19.05 MaxZ31.5 MaxVV THREADM15x1-6g | | | comply with or by a third party I notice.) isdiction & Control List | 2 | |
| N | -Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories | | | FR Not Listed PN: 8D111F02PA | | | |
| | -Temperature Range : -65°C to +200°C -Salt Spray : 48 hours | | A 26-09-2016 | A 26-09-2016 First Release | | | |
| | | | ISS DATE Designed By: | Latest modification - by Date: | CUSTOMER DRAWING | — | |
| | | | TITLE | Aluminium Inline p | lug 8D series | | |
| <u> </u> | BASIC SERIES: 8D 1 - 11 F SHELL TYPE : In line Receptacle I I I I I | 02 P A | SCALE NA | General linear Tolerances: ± | NPRDS / PROJECT 859 | 1 | |
| | CONTACT TYPE : Standard Crimp Contact | | | WWW.SOURIAU.COM | This document is the property of SOURIAU it must not be reproduced or | | |
| | SHELL SIZE : 11 PLATING : F = Nickel | CONTACT TYPE : PIN(5) | OUT : 11-02 | SOURIAU DRG N | communicated without permission SHEET | | |
| | | | A3 | 8D111F02PA-C | 1/2 | | |
| | H G I | F I E | D | C B | I A | | |

| _ | ۲ G | т | ш | | 0 | σ | Þ | - |
|----------|---|---|---|----------------------------|--|--|---|---|
| 4 | Contact Layout | | | | | | | 4 |
| | Contacts (Insert arrangement 11-2) Contact position ID Contact location (mm) Contact location A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00) Shell Arrangement no. Number of contacts Size Service Contact 11 -2 2 16 I All | | | | | | | 3 |
| | | | | | | | | |
| N | | | | | due to a use of the Proc the Specifications issued by e | mendation, technical notice.) Country Jurisdiction | with ird party | 2 |
| | | | | A 26-09-2016 F ISS DATE | | 111F02PA | MOD N° | _ |
| | | | | Designed By: TITLE SCALE | Date: Alum | ninium Inline plug 8D | | _ |
| _ | | | | NA SOURIAU | Toleral ± WWW.SOURI | AU.COM | IPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission | 1 |
| | | - | | FORMAT A3 | 8D1 | RIAU DRG N° 11F02PA-C | SHEET 2/2 | |
| | H G I | F | E | D | C | В | A | |