



- NOTES:
1. ALL DIMENSION IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC  
350mA, 110V AC/DC
  5. CONTACT RATING (NON-SWITCHING) 5A
  6. OPERATING FORCE: 425±100 CM/STANDARD
  7. OPERATING TEMP: -30° to 85°C
  8. CIRCUIT SP: 3 POSITIONS, 90° INDEX.
  9. DIELECTRIC STRENGTH 1000V RMS min.⊗ SEA LEVEL
  10. ▲ DENOTES CRITICAL PARAMETER
  11. HARDWARE SUPPLIED ON SWITCH- SEE BELOW  
STOP RING, LOCKWASHER, & HEXNUT

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	13285	RELEASED FOR PRODUCTION	7/11/03	AR

TITLE	SCALE	DATE	DR	DWG	REV
KC56B10.002NLS	1.5:1	7/11/03	AR	G510999	A

**E-SWITCH®**

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED