

**Specifications:**

|                              |  |
|------------------------------|--|
| <b>Sound Level Category</b>  | Soft   |
| <b>Mode of Operation</b>     | Fast Pulse Rate (10pps)  |
| <b>Voltage Rating</b>        | 48 to 120 VAC/DC   |
| <b>Frequency</b>             | 2900 Hz ±500 Hz  |
| <b>Loudness @ 2 FT</b>       | 65 to 75 dB(A) typ.  |
| <b>Current Draw</b>          | 40 mA Max  |
| <b>Housing Material</b>      | Nylon 6/6 (Color: Black)   |
| <b>Storage Temperature</b>   | -40°C to +85°C   |
| <b>Operating Temperature</b> | -30°C to +65°C   |
| <b>Panel Mounting</b>        | Recommended hole size is 1.25in (31.75mm). Threaded front will fit standard 30mm (1.181in) hole. |
| <b>Knurled Nut</b>           | Used to attach part to panel. The max recommended torque is 10 in-lbs                            |
| <b>Weight (Typical)</b>      | 1.5 oz (43 g)  |
| <b>NEMA 3R, 4X, &amp; 12</b> | Approved with use of ACC03.  |
| <b>Options</b>               | For other options contact factory  |

**Dimensions:** Inches (mm)

**RoHS Compliant**

