

Specifications:

| | |
|-------------------------|------------------------------------|
| Sound level Category | Loud Sound Level |
| Mode of Operation | Slow Pulse |
| Mounting | Panel (see note B) |
| Voltage Rating | 30 to 120 Vac/dc |
| Frequency | 2900 Hz ±500 Hz |
| Loudness (Min. Voltage) | 80 dB(A) min. @ 2 FT and 30 Vac/dc |
| Loudness (Max Voltage) | 95 dB(A) min. @ 2FT and 120 Vac/dc |
| Current Draw | 6 mA Max @ 30 Vac/dc |
| Current Draw | 24 mA Max @ 120 Vac/dc |
| Min Pulse Rate (PPS) | 0.5 @ 30 Vac/dc |
| Max Pulse Rate (PPS) | 2.0 @ 120 Vac/dc |
| Duty Cycle (%) | 50 (Approx) |
| Storage Temperature | -40°C to +85°C |
| Operating Temperature | -30°C to +65°C |
| Weight (Typical) | 2.1 oz (59 g) |
| Housing | 6/6 Nylon, Color Black |
| Options | For other options contact factory |

Dimensions: Inches (mm)



PART DIMENSIONS BEFORE CODE DATE 0824 5

PART DIMENSIONS AFTER CODE DATE 0825 1

