Image: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III: Section MLDT: 3299 Series III: Image: Section MLDT: 3299 Series III:
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal -Shell Material A 34.9±0.3
-Shell Plating : Black Zinc Nickel R 32.5Max due to a use of the Products which does not comply with
Insulator Thermoplastic S 31.8±0.4 the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation, technical notice.) Image: Commendation of the Parties or by a third party (professional recommendation of the Parties or by a third party (professional recommendation of the Parties or by a third party (professional recommendation of the Parties or by a th
-Temperature Range -65°C to +175°C -Salt Spray : 500 hours -Mass : 19.48 g ± 10% ISS DATE Latest modification - by MOD N°
TITLE Aluminium Receptacle 8D series
BASIC SERIES: 8D 7 - 11 Z 05 P B SCALe General linear NPRDS / PROJECT 859 1 SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact ORIENTATION : B NA SCALe NA This document is the property of SOURIAU SOURIAU SOURIAU BS9 1 This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-05 FORMAT SOURIAU DRG N° SHEET H G F E D C B A

	I	G	т	т	D	C	Φ	A	
4	Contact	\oplus^{A} $+x$				Panel cutout JAM NUT RECEPTACLE (TYPE 7)			4
	position ID X-axis (mm) A +.065 (1. B B +.113 (2.5 C C +.000 (0.0 D	V-axis (mm) 5) +.056 (1.42) 7) 065 (1.65) 0) 130 (3.30) 7) 065 (1.65) 5) +.056 (1.42)				ØC			_
ω	11 -5 5 20	I All MS20050-5				DimNominalB19.59+0/-0.25ØC20.96+0.25/-0			3
	_					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either of (professional recommendat	ich does not comply w the Parties or by a thi	ith	
2						Countr FR PN: 8D7112	Not L		2
					A 01-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:	CUST	MOD N	°
					TITLE SCALE NA	Aluminium General linear Tolerances:	NRECEPTACIE 8D	Series PRDS / PROJECT 859	
-					SOURIA	U WWW.SOURIAU.C	COM	his document is the property of SOURIAU it must not be reproduced or ommunicated without permission	
					FORMAT A3	SOURIAU 8D711Z		SHEET 2/2	
	Н	G	F	E	D	С	В	A	