




APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-40°C TO +85°C (NOTE 1) 	STORAGE TEMPERATURE RANGE	-10°C TO +60°C (NOTE 2)
	OPERATING HUMIDITY RANGE 	40% TO 80%	STORAGE HUMIDITY RANGE 	40% TO 70% (NOTE 2)
	VOLTAGE	250V AC	APPLICABLE CABLE	AWG 24 TO 28
	CURRENT	AWG 24~26 : 2 A AWG 28 : 1 A		

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----




#### CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X


#### ELECTRIC CHARACTERISTICS

CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	30 mΩ MAX.	X	-
--------------------	-------------------------	------------	---	---

#### MECHANICAL CHARACTERISTICS

MECHANICAL OPERATION 	30 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
VIBRATION 	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
SHOCK 	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-

#### ENVIRONMENTAL CHARACTERISTICS




RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→+85→ 5 TO 35 °C TIME 30→ 10 → 30→ 10 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
DAMP HEAT (STEADY STATE) 	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-

#### REMARKS

NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT.

NOTE 2:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTSBEFORE PCB ON BOARD.

AFTER PCB BOARD , OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERM STORAGE DURING TRANSPORTATION.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 7	DIS-H-008703	MI. SAKIMURA	TS. KUMAZAWA	14. 04. 24
Unless otherwise specifid , refer to IEC 60512.			APPROVED	KJ. KATAYOSE 05. 01. 05
			CHECKED	TY. OMA 05. 01. 05
			DESIGNED	IO. DENPOUYA 05. 01. 05
			DRAWN	IO. DENPOUYA 05. 01. 05
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-083343-00	
	SPECIFICATION SHEET	PART NO.	DF11-EP2428PCF	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL543-0615-4-00	 1/1