



- NOTES
- ① THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑥ TO BE 3 TO 3.5 N·m.
 - ② THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑩ TO BE 0.2 TO 0.25 N·m.
 - ③ ROTATION EXAMPLES OF REF. NOS. ① AND ⑥ ARE SHOWN.
 - ④ SCREW OF REF. NO. ①, ⑥, ⑩, LOCTITE 263, OR EQUIVALENT, HENKEL JAPAN IS RECOMMENDED TO PREVENT FROM LOOSENING.
 - ⑤ THIS PRODUCT TO BE USED WITH CABLECLAMP, JR16WCC-*(31).
 * DESIGNATE DIAMETER OF APPLICABLE CABLE.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
5	PHOSPHOR BRONZE	NICKEL PLATING	10	STAINLESS STEEL	
4	PHENOL-FORMALDEHYDE	(BLACK) UL94V-0	9	NBR	(BLACK)
3	PHENOL-FORMALDEHYDE	(BLACK) UL94V-0	8	NBR	(BLACK)
2	COPPER ALLOY	SILVER PLATING 3μm min.	7	BRASS	BLACK CHROME PLATING
1	ALUMINUM ALLOY	BLACK CHROME PLATING	6	BRASS	BLACK CHROME PLATING

UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.				APPROVED : HY. KOBAYASHI 18.02.22 CHECKED : HY. KOBAYASHI 18.02.22 DESIGNED : TH. KAMEYA 18.02.22 DRAWN : MK. INOUE 18.02.13	DRAWING NO. EDC-110562-31-00 PART NO. JR16WP-10P(31) CODE NO. CL114-2004-3-31		