

APPLICATOR PARTS LIST

TYPE SIDWISE 1058 DIA
Pin Rept.

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER 453932-3	1	255547	42	SHEAR PLATE -LEFT	1	811855-1
2	INS. CRIMPER	1	1-165261-8	43	SHEAR BLOCK -RIGHT	1	386372
3	ANVIL	1	152618-1	44	FLOATING SHEAR	1	165106
4	ANVIL SPACER FRONT	1	310070-5	45	RETAINING PLATE FRONT	1	811714-2
5	SHEAR BLADE			46	RETAINING PLATE REAR	1	386370
6	REAR SHEAR PLATE			47	SPRING SHEAR RETURN	1	374322
7	REAR ANVIL SPACER	1	152621-1	48	SHEAR DEPRESSOR	1	811101-2
8	FRONT SHEAR PLATE			49	KEY SHEAR RET.	1	386358
9	REAR ANVIL SPACER PLT.			50	GUARD MOUNT	1	811306-1
10	FRONT ANVIL SPACER PLT.			51	HOLDER PUNCH	1	810498-3
11	TOOL SPACER	1	470493-7	52	PUNCH ASSY	1	810738-1
12	CRIMP SPACER	1	375548	53			
13	FRONT STRIP GUIDE	1	810971-1	54	REAR STRIP GUIDE (BOT)	1	811527-3
14	REAR STRIP GUIDE 465440-4	1	165702	55			
15	RAM	1	171912	56			
16	TOOL HOLDER			57			
17	ADJ. CRIMP MOUNT			58			
18	ADJ. BLOCK	1	811102-1	59			
19	APPLICATOR MOUNT ASSY.			60	SCREW, Soc. HD. CAP. A	3	811651-3
20	BASE PLATE	1	165100	61			
21	BASE BLOCK	1	165101	62			
22	STRIP GUIDE PLATE	1	165414-1	63			
23	ANVIL HOLDER			64	1" AIR FEED ASSY	1	690021-1
24	WIRE STOP GUIDE	1	811787-1	65	TENSION ADJ. PL	1	374999
25	STRIPPER -WIRE STOP	1	386361-1	MISCELLANEOUS			
26	STRIPPER MOUNT	1	386362	66	2" DIA. REEL SUPPORT	1	565050-2
27	RETAINER PLATE	1	389078	67	LUBRICATOR ASSY.	1	465184-2
28	STRIPPER MOUNT BRACKET	1	387715-1	68	OIL, SYNTHETIC	1	22014-1
29	STRIPPER BUSHING 389049-1	1	386363	69			
30	STOCK DRAG	1	386955	70			
31	STOCK DRAG HANDLE			71			
32	STOCK DRAG STUD	1	374900	72	DATE CH. FEED ASSY	1	1-492140-3
33	STOCK DRAG SPRING 370572	1	372507	REV. REVISION RECORD			
34	STOCK DRAG Nut	1	21022-3	B	REVISED PER ECN	4/1/67	OF R. L5206
35	FEED FINGER HOLDER	1	386912	C	ADD ITEM 65 67465	5-1-68	RS NY 2-5649
36	FEED FINGER	1	386911	D	26 ADD 1 13744 30218 68 1702	8-4-68	RS NY 1-6189
37	FEED FINGER TIP	1	387251	E	ITEM 33 WAS 373469	10-21-68	L-6225
38	FEED FINGER SPACER Guide Δ	1	689915-2	F	REV. PER ECN	9-8-69	OF NY 16950
39	BASE CASTING	1	570238	G	PER ECN	9-8-70	OF NY 17774
40	GUARD 460881-1	1	811301-1	H	REV. C.H.	3-5-71	NY 18147
41	Bracket Guard	1	811301-1	I	PER ECN	1-24-72	NY 18147
				J	ITEM 1 WAS 1-453932-3	8-9-72	OF NY 19152
				K	REV PER ECN	8-4-75	NY 1-9234
				M	REV PER ECN	7-23-73	JF L-9908

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				60939-
WIRE SIZE	CRIMP HEIGHT			
24	0.034			
22	0.037			
20	0.041			
CRIMP	SIZE	TYPE	FEED	
WIRE	.055	F		
INSUL.	.090	0	.255	
SLEEVED				
INSULATION RANGE		WIRE RANGE		
.060-.090 DIA.		24-20		
EXPLODED VIEW				
A-6002-6		A-6002-10		
REMARKS:				
Δ MT. ON ITEM 13				
Δ USE WITH ITEM 25 18				

INACTIVE
FOR REPLACEMENT ONLY

DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT		
THIS APPLICATOR IS TO BE USED ON		
AMP-O-ELECTRIC	1-471272-2	DIST. 4
AMP-O-MATE	1-492140-3	DESIGNED BY R1 4-4-66
SERIAL NO.	DATE SHIPPED	CHK'D BY 4-4-66
CUSTOMER NAME AND ADDRESS		APP'D BY 4-4-66
APPLICATOR NUMBER	REV. NY 565706-1	SHEET 1 OF 1

N PER ECN 3-10-72 28 2514
NI INACTIVE 2-24-73 68 2514
M REV PER ECN 7-23-73 JF L-9908

FOR HARDWARE
SEE 687511-2