

INTERNAL THREAD UNC 4.40

5 across flats

3.3 MINL
4.2 ±0.1

4.60 +0.1
-0.1

8.30 +0
-0.1

6.90 ±0.1

0.8 ±0.1

M3

1.00 ±0.1

0.8 ±0.1

1.80 ±0.1

0 10 MM

NOTES

Material : steel yellow cadmium plated

Corrosion resistance : 24 hours exposure to salt spray

Packaging by 100 pieces

Part number 86552153

European Views

www.fciconnect.com		surface ISO 1302	tolerance std ISO 406 ISO 1101	projection 	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
ANGULAR	LINEAR	0.X	±0.1	size A3	Scale 10
0.XX' ±2'		0.XXX	±0.1	ECN LS08-0232	
Dr MASSON	2000/08/28	Product family		D-SUB	Spec ref -
Eng PESSON	2000/08/28				
Chr LEGARE	2000/08/28				
Appr LEGARE	2000/08/28				
	title FEMALE SCREW LOCKS			dwg no C01-8655-1545	Rev. C
	catalog no	-	CUSTOMER	sheet 1 of 1	

rev	ecn no	dr	date
A	-	MAS	2000/08/28
B	LS06-0097	LGO	2006/07/28
C	LS08-0232	MPE	2008/12/16
-	-	-	-
-	-	-	-
-	-	-	-