



ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
lex	@ 18.5V, 3.2mA DC, 400Hz, Pin 1 - Pin 3	1mA Max.
Sec. N.L.V	@ 18.5V, 400Hz, Pin 1 - Pin 3	
	Pin 4 - Pin 5 =	4.149V ±2%
	Pin 5 - Pin 6 =	4.149V ±2%
	Pin 4 - Pin 6 =	8.298V ±2%
Polarity	Pin 1, Pin 4	Additive
DCR	@ 20°C, Pin 1 - Pin 3 =	598.7 Ω ±20%
	@ 20°C, Pin 4 - Pin 6 =	79.19 Ω ±20%
HIPOT	PRIMARY - SECONDARY	250V, 60Hz, 1 SEC

REV.#	REVISION	DATE	HAMMOND ELECTRONIC DIVISION 52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5			PH # (519) 886-6181 FAX # (519) 886-9540
0	RELEASED.	01/13/11	DWG. BY: C. ILIE	CHK'D BY:	TITLE: 104H	DWG. NO.
			DATE: 01/13/11	APP'D. BY:	TRANSFORMER	EDB104H
				DIMENSIONS: IN(X) MM()		