



注記
NOTES

1. 各部の反りは0.5最大。
WARPING : 0.5 MAX.
2. サーマットNO.はNO.*I"のみ表示。
CIRCUIT NO. : I ONLY.

44.7	39.6	09-50-1104	5196-102	10
36.78	31.68	09-50-1084	5196-082	8
B	A	EDP. NO.	MATERIAL NO.	NO. OF CKTS.
			MODEL NO.	5196-N2

REVISED EC NO: J2009-0871 DRWN: MAKURAA 2008/12/08 CHKD: T. HARUYAMA 2008/12/08 APPR: NUKITA 2008/12/12	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	10 UNDER	±0.2	DRAWN BY	DATE	TITLE	
	10 OVER 30 UNDER	±0.25	CHECKED BY	DATE	SPOX 7.92/3.96 PITCH RECEPTACLE HOUSING	
	30 OVER	±0.3	APPROVED BY	DATE		
ANGULAR	±3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		M. FUKUSHIMA '96/4/10 MATERIAL NO.	MOLEX INCORPORATED DOCUMENT NO.	SHEET NO. 1 OF 1
SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

材料
MATERIAL
ナイロン66, UL94V-2
NYLON66, UL94V-2