


HC-M-KV-M20(11-16)

Order No.: 1645998



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1645998>

Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20

| Commercial data | |
|--------------------------|--|
| GTIN (EAN) |  |
| sales group | D092 |
| Pack | 25 pcs. |
| Customs tariff | 74199990 |
| Catalog page information | Page 521 (PC-2009) |

Product notes

WEEE/RoHS-compliant since:
06/16/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

| General data | |
|------------------------|---------------------|
| Cable gland material | Nickel-plated brass |
| Seal material | Neoprene |
| Cable seal material | Neoprene |
| Material, O-ring | NBR |
| Wrench size, union nut | 27 mm |

| | |
|---------------------------------|-----------------------|
| Wrench size, support | 27 mm |
| Thread type connection side 1 | M20 |
| Length of the connecting thread | 6.00 mm |
| External cable diameter | 11 mm ... 16 mm |
| Conductor sealing range | 11.00 mm ... 16.00 mm |
| Tightening torque, union nut | 7.50 Nm |
| Degree of protection | IP68, to 5 bar |
| Ambient temperature (operation) | -20 °C ... 100 °C |

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;