

## Specification Sheet

Part Number: 166-90375



HelGuard AFCP Smooth Tubing Clip, 0.50" Dia, PA66, Black, 10/pkg

|                                |   |
|--------------------------------|---|
| <b>Article Number</b>          | 166-90375   |
| <b>Type</b>                    | AFCP0500  |
| <b>Color</b>                   | Black (BK)  |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Integrated flip open lid for quick and easy assembly.</li><li>• Smooth inner surface holds tubing from slipping.</li><li>• Easy access mounting hole reduces installation time.</li><li>• Quick release for easy future access.</li></ul> |
| <b>Quantity Per</b>            | pack  |
| <b>Product Description</b>     | Conduit Clips clamp onto corrugated conduits and tubing to secure. Nylon material resists corrosion and chemicals. Can also be used on C-shaped DIN rails.  |
| <b>Short Description</b>       | HelGuard AFCP Smooth Tubing Clip, 0.50" Dia, PA66, Black, 10/pkg  |
| <b>Global Part Name</b>        | AFCP0500-PA66-BK  |

|  |                      |
|--|----------------------|
| <b>Length L (Imperial)</b>                   | 1.26                 |
| <b>Length L (Metric)</b>                     | 32                   |
| <b>Variant</b>                               | Clip                 |
| <b>Width W (Imperial)</b>                    | 0.59                 |
| <b>Width W (Metric)</b>                      | 15                   |
| <b>Height H (Imperial)</b>                   | 1.42                 |
| <b>Height H (Metric)</b>                     | 36                   |
| <b>Nominal Diameter (Imperial)</b>           | 1/2                  |
| <b>Nominal Diameter (Metric)</b>             | 20                   |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.24                 |
| <b>Mounting Hole Diameter D (Metric)</b>     | 6.0 mm               |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 6                    |
| <b>Material</b>                              | Polyamide 6.6 (PA66) |
| <b>Material Shortcut</b>                     | PA66                 |
| <b>Flammability</b>                          | UL 94 V2             |

**Operating Temperature (Metric)**

-58°F to +275°F (-50°C to +135°C)

**Package Quantity(Imperial)**

10

**Package Quantity (Metric)**

10