E G T	m	D	0	B	_
	S		<image/> <image/>	<image/>	4
Keving S	Shown as example				
CHARACTERISTICS	Connector dimension				
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	DimNominalA38.1±0.3B23.82+0.1/-0.15R32.5MaxS34.9±0.4W2.2+0.9/-0.1VV THREADM18x1-6g		SOURIAU shall not be liable for any ne due to a use of the Products which the Specifications issued by either of th (professional recommendation Country	n does not comply with e Parties or by a third party	
 Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles 			FR	Not Listed	2
-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C					
-Salt Spray : 500 hours 		ISS DATE	First Release Latest modification - by	MOD N°	•
		Designed By:	Date: Aluminium R	customer drawing Receptacle 8D series	
BASIC SERIES: 8D 7 - 13 W 26 P	в	SCALE	General linear	NPRDS / PROJECT	_
SHELL TYPE : Jam nut Receptacle		NA	Tolerances:	859 This document is the property of	1
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENTATION : B CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.CO	COLIDIALI	
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-26	FORMAT A3	SOURIAU D	DRG N° SHEET	
H G F	E		8D713W2	6PB-C 1/2 B A	

Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series Image: Customer desceptacle 8D series SCALE Image: Customer desceptacle 8D series Image: Customer desceptacle 8D series NA Image: Customer desceptacle 8D series Image: Customer desceptacle 8D series SOURIAU Image: Customer desceptacle 8D series Image: Customer desceptacle 8D series NA Image: Customer desceptacle 8D series Image: Customer desceptacle 8D series SOURIAU Image: Customer desceptacle 8D series Image: Customer desceptacle 8D series SOURIAU Image: Customer desceptacle 8D series Image: Customer desceptacle 8D series FORMAT SOURIAU.COM Image: Customer desceptacle 8D series FORMAT SOURIAU DRG N° SHE	r	Т	۵	г т	п	D C B A		
Image: Solution of the second state of the	4	(26			JAM NUT RECEPTACLE (TYPE 7)	4	
No		A B C D E F 1	6#22D 13-26 X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 4.34 3.25 0			Dim Nominal B 24.26+0/-0.25	3	-
Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series SCALE General linear Tolerances: NPRDS / PROJECT NA Tolerances: 859 ± This document is the property of SOURIAU SOURIAU.COM FORMAT SOURIAU DRG N° SHE	N					due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D713W26PB A 29-09-2016 First Release	2 MOD N°	
A3 8D713W26PB-C 2/						Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series SCALE General linear NPRDS / PROJECT NA Tolerances: 859 This document is the proper SOURIAU FORMAT SOURIAU DRG N°	rty of I or	1