



REVISIONS			
ISS	ZONE	DESCRIPTION	PER REQUEST DATE
A2	A-2	NO.1 WAS CHANGED	N/A\10-29-02'

REMARK: 1. AFTER FORM OVER, CENTER CONTACT SHALL NOT ROTATE RELATIVE TO BODY A TORQUE OF 4 IN-OZ.  
 (全周成型後, 中心針與主體間須能承受 4 IN-OZ 的扭力)  
 2. INSULATOR MUST WITHSTAND AN 8 LB PUSH-OUT FORCE FROM BODY.  
 (絕緣體與主體間需能承受 8 LB 的推力)

FORM OVER ALL AROUND  
 DO NOT BREAK THRU PLATING.  
 (全周成型不可破壞電鍍)  
 (SEE REMARK 1,2)

SOLDER POCKET ORIENTATION IS OPTIONAL  
 (焊接口的方向可隨意)

STAMP "74868 UG-625/U"  
 IN 1.6mm HIGH DEPRESSED CHARACTERS  
 (戳字"74868 UG-625/U" 字高1.6mm)

1. MAX. PANEL THICKNESS=3.96mm

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 3. BERYLLIUM COPPER PER QQ-B-530  
 4. SILVER PL. 200 MIN. THICK OVER COPPER STRIKE  
 5. TEFLON MIL-P-19468  
 6. PHOSPHOR BRONZE PER QQ-B-750

RECOMMENDED MOUNTING HOLE  
 (建議架設孔)

DIMENSIONS ARE IN MILLIMETERS				PART NO.		<b>Amphenol</b> Danbury, CT, USA - Tainan, Taiwan - Shenzhen, China	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE		
0.5-6 = ±0.2				<i>Tony</i>	10-30-02'	TITLE BNC BULKHEAD RECEPT. JACK FRONT MOUNT (FOR UG-625/U)	
6-30 = ±0.4				CHECKED	DATE	DRAWING NO. 5575	
30-120 = ±0.6				<i>Roemer</i>	10-30-02'	ITEM NO. 5575	
120-315 = ±1				DRAWN	DATE	FILE NO. F:\DWG\CNPD\5575SZ	
315-1000 = ±1.6				<i>Rochel</i>	10-30-02'		
1000-2000 = ±2.4							

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
5	HEX NUT			1	HN127-3/8-32X23
4	LOCK WASHER			1	LW-127/97X05PB
3	CONTACT PIN			1	31-10124
2	INSULATOR		NATURAL	1	31-10125-1
1	BODY			1	31-1391