

## Specification Sheet

Part Number: 558-00069



SwiftMark Self-Laminating Label, 1.0" x .35" x 1.0", VL, White, 5000/roll

<b>Article Number</b>	558-00069
<b>Type</b>	TAG26-53W254SM
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.</li><li>• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li><li>• Labels are UL recognized for indoor and outdoor use to expand application options.</li><li>• HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.</li></ul>
<b>Quantity Per</b>	roll

**Product Description**

HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

**Short Description**

SwiftMark Self-Laminating Label, 1.0" x .35" x 1.0", VL, White, 5000/roll

**Global Part Name**

TAG26-53W254SM-100B-WH

**Technical Description**

SwiftMark Self-Laminating Label, 1.0" X .35" X 1.0", White

**Variant**

Roller form

**Width W (Imperial)**

1.0

**Width W (Metric)**

25.4

**Bundle Diameter Min (Imperial)**

.21

**Bundle Diameter Min (Metric)**

5.50

**Bundle Diameter Max (Imperial)**

0.47

**Bundle Diameter Max (Metric)**

11.94

**Thickness T (Metric)**

25

**Height H (Imperial)**

0.75

**Height H (Metric)** 19.05

**Width of Liner (Metric)** 28.57

**Width of Liner (imperial)** 1.125

**Outside Diameter Max(Imperial)** 0.2

**Outside Diameter Min (metric)** 2.6

**Outside Diameter Min(Imperial)** 0.1

**Outside Diameter Max (metric)** 5.3

**Material** Type 100, Vinyl (PVC), white (WH), self laminating

**Material Shortcut** 100B

**Adhesive** Acrylic

**Adhesive Operating Temperature** -40°F to +194°F (-40°C to +90°C)

**Operating Temperature (Metric)** -40°F to +176°F (-40°C to +80°C)

**ROHS Complaint** Yes

**Certification/Specification WEB** UL-Recognized

**UL Recognized (US)** Yes

<b>Package Quantity(Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Customs Number</b>	3919102055
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	1.09
<b>Weight (Imperial)</b>	2.40