

	Ξ		A			
	C				4	
AS EXA	AMPLE				3	
s which er of t ndation untry FR	non-conformit ch does not co che Parties or b on, technical no Jurisd	mply with by a third part			2	
ar J.CC	MOD N°   CUSTOMER DRAWING   Steel Plug 8D series   NPRDS / PROJECT   859   This document is the property of SOURIAU   SOURIAU   it must not be reproduced or communicated without permission   DRG N°   SHEET   3BN-C					
	В		А		1	

-	Ŧ	۵	г П	m	D	0
		Contact Layout				
4	*	<b>Γ</b> <b>Λ</b> <b>Λ</b> <b>Λ</b> <b>Λ</b> <b>Λ</b> <b>Λ</b> <b>Λ</b> <b>Λ</b>				
	B + 225 (5.72) C + 336 (8.53) D + 450 (11.43) E + 450 (11.43) F + 450 (11.43) G + 336 (8.53) H + 225 (5.72) J - 225 (5.72)	Y-axis (mm)   Contact postion ID   X-axis (mm)   Y-axis (mm)     455 (11.56)   g   -225 (5.72)   -260 (6.60)     +336 (9.91)   f   -336 (8.53)   -169 (4.95)     +325 (8.26)   g   -336 (8.53)   -065 (1.65)     +130 (3.30)   h   -336 (8.53)   +065 (1.65)     -130 (3.30)   m   -225 (5.72)   +280 (6.60)     -325 (8.26)   n   -112 (2.84)   +325 (8.26)     -130 (3.30)   m   -225 (5.72)   +280 (6.60)     -325 (8.26)   n   -112 (2.84)   +325 (8.26)     -410 (10.41)   p   +000 (0.00)   +280 (6.60)     -410 (10.41)   q   +112 (2.84)   +395 (4.95)     -326 (8.26)   f   +225 (7.27)   +730 (3.30)				
ω	M  450 (11.43)     N  450 (11.43)     P  336 (8.53)     R  225 (5.72)     S  112 (2.84)     T   +.000 (0.00)     U   +.112 (2.84)     V   +.225 (5.72)     Contact   Locativ     position   X-axis	+.000 (0.00)   1   +225 (5.72)  130 (3.30)     +.130 (3.30)   y   +.112 (2.84)  195 (4.95)     +.326 (8.26)   y   +.000 (0.00)  260 (6.60)     +.390 (9.91)   w  112 (2.84)  195 (4.95)     +.455 (11.56)   x  225 (5.72)  130 (3.30)     +.455 (15.60)   x  225 (5.72)  130 (3.30)     +.390 (9.91)   y  225 (5.72)   +.130 (3.30)     +.256 (8.60)   Z  225 (5.72)   +.130 (3.30)     +.266 (6.60)   AA  112 (2.84)   +.195 (4.95)     Contacts   (Insert arrangement 23-53)  112 (3.93)				
	X +.336 (8.53) Y +.336 (8.53) Z +.336 (8.53) <u>a</u> +.225 (5.72) <u>b</u> +.112 (2.84) <u>c</u> +.000 (0.00) <u>d</u> 112 (2.84) Shell Arrangement Num size no. con	(mm)   (mm)   (mm)   (mm)     +195 (4.95)   BB   +.000 (0.00)   +.130 (3.30)     +065 (1.65)   CC   +.112 (2.84)   +.005 (1.65)     -095 (1.65)   DD   +.112 (2.84)  005 (1.65)     -195 (4.95)   EE   +.000 (0.00)  130 (3.30)     -260 (6.60)   FF  112 (2.84)  005 (1.65)     -326 (6.60)   FF  112 (2.84)  005 (1.65)     -320 (9.20)   O'S  112 (2.84)  005 (1.05)     -320 (9.21)   HH   +.000 (0.00)   +.000 (0.00)     -320 (8.26)				SOURIAU shall not be liable for an due to a use of the Products w
N						the Specifications issued by either o (professional recommenda Count FR
					A 07-10-20 ISS DATE Designed By:	PN: 8D523 16 First Release Latest modification - by Date:
					TITLE SCALE NA	General linear Tolerances:
					SOURIAI	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D523S
L	Н	G	F	E	D	C

