

## Specification Sheet

Part Number: IT50R10C2

**HellermannTyton** Identification Tie, 8" Long, 50lb Tensile Strength, PA66, White, 100/pkg

<b>Article Number</b>	111-85027
<b>Type</b>	IT50R
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Identification plate feature allows bundles to be easily marked and identified.</li><li>• Wire and cable harnesses can be secured and identified using just one product, which saves time.</li><li>• Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Identification Cable Ties feature an identification plate that allows wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.
<b>Short Description</b>	Identification Tie, 8" Long, 50lb Tensile Strength, PA66, White, 100/pkg

Global Part Name

IT50R-PA66-WH

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

8.0

Length L (Metric)

203.0

Identification Plate Position

attached to bundle

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

1.1

Width W (Metric)

28.0

Bundle Diameter Min (Imperial)

0.37

Bundle Diameter Min (Metric)

9.5

Bundle Diameter Max (Imperial)

1.8

Bundle Diameter Max (Metric)

44.5

Height H (Imperial)

0.51

Height H (Metric)

12.9

Outside Diameter Max(Imperial)

1.73

<b>Outside Diameter Min (metric)</b>	9.50
--------------------------------------	------

<b>Outside Diameter Min(Imperial)</b>	0.37
---------------------------------------	------

<b>Outside Diameter Max (metric)</b>	44.50
--------------------------------------	-------

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

<b>Material Shortcut</b>	PA66
--------------------------	------

<b>Flammability</b>	UL 94 V2
---------------------	----------

<b>Halogen free</b>	Yes
---------------------	-----

<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
---------------------------------------	----------------------------------

<b>Reach Complaint(Article 33)</b>	No
------------------------------------	----

<b>ROHS Complaint</b>	Yes
-----------------------	-----

<b>Certification/Specification WEB</b>	UL
--	----

<b>UL Recognized (US)</b>	Yes
---------------------------	-----

<b>UL Recognized (US and Canada)</b>	Yes
--------------------------------------	-----

<b>Package Quantity(Imperial)</b>	100
-----------------------------------	-----

<b>Package Quantity (Metric)</b>	100
----------------------------------	-----

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)