

Distributor - VS-ASI-J-Y-B-FFKDS - 1404498

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



AS-Interface distributor with IP20 degree of protection for two flat-ribbon conductors, with spring-cage terminal blocks for four litz wires up to 1.5 mm²



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	26.1 GRM
Custom tariff number	85366990
Country of origin	Vietnam

Technical data

Mechanical characteristics

Number of positions	4
Connection method	AS-i penetration technique
Conductor cross section	0.2 mm ² ... 1.5 mm ²
	0.25 mm ² ... 0.75 mm ² (With ferrules)
Connection cross section AWG	24 ... 16
	23 ... 18 (With ferrules)
Color	black
Tightening torque, min.	1.65 Nm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 75 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Degree of protection	IP20

Material data

Housing material	PA-GF
------------------	-------

Distributor - VS-ASI-J-Y-B-FFKDS - 1404498

Technical data

Material data

Contact carrier material	TPE-U
Contact material	CuZn
Contact surface material	Ni/Au
Material	CuSn (Leg spring)
	PA (Spring-cage terminal block housing)
	Tin-plated (Leg spring contact surface)

Electrical characteristics

Rated voltage (III/3)	≤ 35 V
Rated current	≤ 6 A

Classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27449001

ETIM

ETIM 2.0	EC000200
ETIM 3.0	EC001856
ETIM 4.0	EC000313
ETIM 5.0	EC000313

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Drawings

Distributor - VS-ASI-J-Y-B-FFKDS - 1404498

Dimensioned drawing

