

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△							△				
△							△				

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		-35 °C TO +85 °C(NOTE1)	STORAGE TEMPERATURE RANGE		-10 °C TO +60 °C	
RATING	VOLTAGE		150 V AC		APPLICABLE CONTACT		-	
	CURRENT		1 A		APPLICABLE CONNECTOR		DF13-*DP-1.25C	
					APPLICABLE CABLE		-	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="radio"/>	<input type="radio"/>
MARKING	CONFIRMED VISUALLY.		<input type="radio"/>	<input type="radio"/>

ELECTRIC CHARACTERISTICS

CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	30 mΩ MAX.	<input type="radio"/>	<input type="checkbox"/>
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD	20 mV MAX, mA(DC OR 1000 Hz).		<input type="checkbox"/>	<input type="checkbox"/>
INSULATION RESISTANCE	100 V DC.	500 MΩ MIN.	<input type="radio"/>	<input type="checkbox"/>
VOLTAGE PROOF	500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	<input type="radio"/>	<input type="checkbox"/>

MECHANICAL CHARACTERISTICS

CONTACT INSERTION AND EXTRACTION FORCES	<input type="checkbox"/> 0.35±0.002 BY STEEL GAUGE.	INSERTION FORCE 3.9 N MAX. EXTRACTION FORCE 0.3 N MIN.	<input type="radio"/>	<input type="checkbox"/>
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE _____ N MAX. EXTRACTION FORCE _____ N MIN.	<input type="checkbox"/>	<input type="checkbox"/>
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	<input type="radio"/>	<input type="checkbox"/>
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, - m/s ² AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs.	<input type="radio"/>	<input type="checkbox"/>
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	② CONTACT RESISTANCE: - mΩ MAX. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	<input type="radio"/>	<input type="checkbox"/>

ENVIRONMENTAL CHARACTERISTICS

RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 5 ~ 35 → +85 → 5 ~ 35 °C TIME 30 → 10 → 30 → 10 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	<input type="radio"/>	<input type="checkbox"/>
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	<input type="radio"/>	<input type="checkbox"/>
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, °C, FOR IMMERSION, DURATION, s.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	<input type="checkbox"/>	<input type="checkbox"/>
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, s.	SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.	<input type="checkbox"/>	<input type="checkbox"/>

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.	<i>H. Umehara</i>	<i>H. Umehara</i>	<i>J. Ona</i>	<i>M. Yamamoto</i>	
Unless otherwise specified, refer to MIL-STD-1344.	197.3.3	197.3.3	97.3.4	97.3.4	

Note QT:Qualification Test AT:Assurance Test ○:Applicable Test

HRS HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.	DF13-*DS*-1.25C
CODE NO.(OLD)	DRAWING NO.	PART NO.	
CL	ELC4-160109-03	CL	536

Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

TO

