


Metal Core SMD Power Inductors (MCOIL™, MD series)

MDKK1616T1R5MM



■ Features

- Item Summary
1.5uH±20%, 1.1A, 1.64x1.64x1.0mm
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 2500pcs

■ Products characteristics table

Inductance	1.5 uH ± 20 %
Case Size (mm)	1.64x1.64
Rated Current (max)	1.1 A
Saturation Current (max)	1.75 A
Saturation Current (typ)	2.2 A
Temperature Rise Current (max)	1.1 A
Temperature Rise Current (typ)	1.33 A
DC Resistance (max)	0.185 Ω
DC Resistance (typ)	0.16 Ω
LQ Measuring Frequency	1 MHz
Operating Temp. Range	-40 to +125 °C (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 10 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow


■ External Dimensions

Dimension L	1.64 ± 0.1 mm
Dimension W	1.64 ± 0.1 mm
Dimension H	Max 1.0 mm
Dimension e	0.4 + 0.2/-0.1 mm
Dimension f	1.0 ± 0.2 mm

■ Recommended Land Patterns

【推奨ランドパターン】
実装上の注意
・実装状態を確認の上ご使用くださいますようお願いいたします。
・本製品のはんだ付けはリフローはんだ工法に限りします。

【Recommended Land Patterns】
Surface Mounting
・Mounting and soldering conditions should be checked beforehand.
・Applicable soldering process to these products is reflow soldering only.



Metal Core SMD Power Inductors (MCOIL™, MD series)




MCOIL™

MDKK1616T1R5MM



Dimension	unit : mm	unit : inch
Length :	1.64 +/- 0.1	(0.065 +/- 0.004)
Width :	1.64 +/- 0.1	(0.065 +/- 0.004)
Height :	1.0 max.	(0.039 max.)

Inductance :	1.5	uH	(test freq at 1MHz)
DC Resistance :	0.160 / 0.185	ohm	(typ / max)
Saturation Current :	2,200 / 1,750	mA	(typ / max)
Temp. rise Current :	1,330 / 1,100	mA	(typ / max)
Saturation current typical : 30% reduction from initial L value.			
Temp rise Current typical : Temperature will rise by 40 deg C			
Maximum rated voltage : DC 25 V			



The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.