



5.0 GHz VERTICAL POLARIZATION HIGH-PERFORMANCE 60° SECTOR

The Laird J51017V00-60N 5.0 GHz wideband, vertically polarized 60° sector antenna, covers frequencies from 4.9 to 5.9 GHz. Extremely low-side lobes, null fill below the horizon and uniform energy distribution with the coverage area are achieved thanks to our highly skilled engineering staff and the utilization of our proprietary Artificial Intelligence RF Optimizing development tool. The antenna meets all aspects of ETSI EN 302.326-3 SS3. The Laird suite of high-performance sector antennas features proprietary design elements, resulting in extremely high levels of system performance and ruggedness while maintaining very slim profiles with low wind and ice loading.



FEATURES

- 4.9 to 5.9 GHz full-band coverage
- Ultra-low side lobe performance
- Maximum null fill below the horizon
- Uniform cell coverage
- Rugged carrier class construction

MARKETS


- High multi-path environment
- Large carrier class deployment
- Wireless broadband service provider
- Optimized for MIMO space time processing

ANTENNA PATTERNS



SPECIFICATIONS

PARAMETER	SPECIFICATIONS
Antenna part number	J51017V00-60N
Frequency range	4.9-5.9 GHz
Peak gain	17.5 dBi (17 dBi typical)
Minimum gain	16.5 dBi @ 5.15-5.3 GHz, 16 dBi @ 4.9 GHz
Maximum VSWR	1.7:1
3 dB beamwidth- Azimuth	60°
3 dB beamwidth- Elevation	7°
Front-to-back ratio	> 35 dB
Azimuth and elevation sidelobes	ETSI 302.326-3 SS3, SS2 @ 4.9 GHz
Cross-polarization	ETSI EN 302.326-3 SS3
Elevation null fill	Down to -25°
Polarization	Vertical
Input impedance	50 ohm
Maximum input power	20 W average, 240 W peak
Mounting hardware	Tilt mount kit 1.5 in to 4.5 in dia.
Lightning protection	DC-grounded
Temperature	-40°C to +70°C
Mechanical size	18.2 in x 4.7 in x 2.8 in
Antenna weight	1.2 kg
Wind survival rating	Operational 100 mph/ Survival 136 mph
Antenna connection	Type N female
Radome	ASA / Aluminum
Mount style	Most mount



**Mounting Kit:
JBXRK-01-TM5**

ANT-DS-J51017V00-60N 112514

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2014 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.