

Fuse - VF-SI/TR5/1AT - 2901005

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in fuse (TR5[®]), nominal current: 1 A, tripping characteristic: slow-blow (T), packing volume per unit: 8 pcs.

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	10.0 g
Custom tariff number	85361010
Country of origin	China

Technical data

General

Nominal voltage U_N	≤ 250 V AC/DC
Fuse	1 A Slow-blow

Classifications

eCl@ss

eCl@ss 4.0	27142098
eCl@ss 4.1	27142098
eCl@ss 5.0	27142007
eCl@ss 5.1	27142001
eCl@ss 6.0	27142001
eCl@ss 7.0	27142001

ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000035
ETIM 4.0	EC000035
ETIM 5.0	EC001423

Fuse - VF-SI/TR5/1AT - 2901005

Classifications

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC
