

## Specification Sheet

Part Number: 156-00865



Outside Serrated Cable Tie & Edge Clip, 5.9" Long, EC5A, 1–3 mm Panel, 50lb, PA66HS, Black, 500/pkg

|                     |  |
|---------------------|--|
| Article Number      | 156-00865  |
| Type                | T50SOSEC5A   |
| Color               | Black (BK)   |
| Features & Benefits | <ul style="list-style-type: none"><li>•Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.</li><li>•Edge Clip provides low insertion force and high extraction force ideal for assembly environments.</li><li>•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.</li><li>•Cable tie is outside serrated to reduce bundle chafing.</li></ul> |
| Quantity Per        | bag  |

### Product Description

HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

**Short Description**

Outside Serrated Cable Tie &amp; Edge Clip, 5.9" Long, EC5A, 1-3 mm Panel, 50lb, PA66HS, Black, 500/pkg

**Global Part Name**

T50SOSEC5A-PA66HS/PA66HIRHS-BK

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

6.0

**Length L (Metric)**

150.0

**Fixation Method**

EdgeClip, sideways, assembled, 2 piece

**Identification Plate Position**

none

**Releasable Closure**

No

**Variant**

Outside Serrated

**Width W (Imperial)**

0.18

**Width W (Metric)**

4.6

**Bundle Diameter Min (Imperial)**

0.20

**Bundle Diameter Min (Metric)**

5.0

**Bundle Diameter Max (Imperial)**

1.4

**Bundle Diameter Max (Metric)**

35.0

|                                       |   |
|---------------------------------------|---|
| <b>Thickness T (Imperial)</b>         | 0.05  |
| <b>Thickness T (Metric)</b>           | 1.2   |
| <b>Height H (Imperial)</b>            | .50   |
| <b>Height H (Metric)</b>              | 1.30  |
| <b>Panel Thickness Min(Imperial)</b>  | 0.04  |
| <b>Panel Thickness Max(Imperial)</b>  | 0.12  |
| <b>Panel Thickness Min (Metric)</b>   | 1.0   |
| <b>Panel Thickness Max (Metric)</b>   | 3.0   |
| <b>Material</b>                       | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>              | PA66HIRHS PA66HS  |
| <b>Material Cable Tie</b>             | Polyamide 6.6 heat stabilized (PA66HS)  |
| <b>Flammability</b>                   | UL 94 HB  |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C) -40°F to +230°F (-40°C to +110°C)                                     |
| <b>ROHS Complaint</b>                 | Yes   |
| <b>Package Quantity(Imperial)</b>     | 500   |

**Package Quantity (Metric)**

500

**Customs Number**

3926909987

**Weight (Metric)**

4.5