



ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^{\circ}\text{C}$ $I_f=20\text{mA}$

PARAMETER	RED	YELLOW	GREEN	BLUE	UNITS	TEST COND
PEAK WAVELENGTH	635	585	565	430	nm	
FORWARD VOLTAGE (TYP.)	2.0	2.1	2.2	4.5	V _f	
FORWARD VOLTAGE (MAX.)	2.5	2.5	2.6	5.5	V _f	
REVERSE VOLTAGE	5.0	5.0	5.0	5.0	V _r	I _r =100μA
AXIAL INTENSITY	30	30	30	30	mcd	I _f =20mA
VIEWING ANGLE	60	60	60	60	2x theta	
LED POSITION:	1	2	3	4		
EPOXY LENS FINISH: DIFFUSED SAME AS EMITTED COLOR						

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	COLORS	MAX	UNITS
PEAK FORWARD CURRENT*		150	mA
STEADY CURRENT	(I/Y/G/B)	30/30/25/30	mA
POWER DISSIPATION		105	mW
DERATE FROM 25°C		-1.6	mW/°C
OPERATING, STORAGE TEMP.		-40 TO +85	°C
SOLDERING TEMP.		+260	°C
2.0mm FROM BODY			3 SEC. MAX

* t<10μS

CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=+DECIMAL PRECISION MAX.=+0.00 -DECIMAL PRECISION

REV.	PART NUMBER SSF-LXH475IYGSBD
T-3mm (T-1) FOUR UNIT FAULT INDICATOR, POS. 1: RED LED, POS. 2: YELLOW LED, POS. 3: GREEN LED, POS. 4: BLUE LED, DIFFUSED PER COLOR.	

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

		290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw	
DRAWN BY: KS/CT	CHECKED BY:	APPROVED BY:	DATE: 3.5.01 PAGE: 1 OF 1 SCALE: N/A