

Specification Sheet

Part Number: T120RSM0HIRK2



Stud Mount Tie for .25", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg

Article Number	157-01300
Type	T120RSM
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•Covers top of stud for protection from stud end.•Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.•PA46 material option allows use in high-heat applications.
Quantity Per	bag
Product Description	HellermannTyton stud mount tie designed for use on a 1/4" threaded stud or exposed threads of a machine screw.
Short Description	Stud Mount Tie for .25", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg

Global Part Name

T120RSM-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535

Length L (Imperial)

16.0

Length L (Metric)

405.0

Fixation Method

Weld Stud Fixing

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.3

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.2

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

4.0

Bundle Diameter Max (Metric)

101.0

Height H (Imperial)

.77

Height H (Metric)	19.50
Stud Diameter (Metric)	6.3 mm
Stud Diameter (Imperial)	0.25
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909987
Content Unit(BMEcat)	bag

