


SECTION V-V
(DYNAMIC CONTACT)

SECT C-C

MATED CONDITION



THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
mm			
0 PLC	± 0.25	0 PLC	± 0.25
1 PLC	± 0.25	1 PLC	± 0.25
2 PLC	± 0.25	2 PLC	± 0.25
3 PLC	± 0.25	3 PLC	± 0.25
4 PLC	± 0.25	4 PLC	± 0.25
ANGLES	± 3'	ANGLES	± 3'

NOTES:
1. APPLICABLE CONNECTOR & CONTACTS:

CIRCUIT TYPE	FINISH	AWG	APPLICABLE CONNECTOR/P/N	REMARKS
HIGH CURRENT CIRCUITS	GOLD PLT	#10-12	179956-X	STRIP
		#14-16	179955-X	STRIP

2. MATERIAL:
HOUSING: PBT G.F. UL94V-0 COLOR: BLACK
MATING COUNTER P/N: 292352-1
4. RECOMMENDED SCREW LOCKING TORQUE: 10~15kgf_cm (0.98~1.47Nm)

PANEL CUT DIMENSIONS
(CONNECTOR MATING SIDE)
RECOMMENDED PANEL THK: 1.0~1.6mm

DMN	ROY HAO	09APR04	09APR04	Tyco Electronics Corporation
CHK	STEVEN YAO	09APR04	09APR04	Shanghai, P.R.China, 200233
APP'D	TSASAKI	09APR04	09APR04	
PRODUCT SPEC	108-51030			REC HOUSING FOR 1.5mm PITCH MINI CT
APPLICATION SPEC	114-51009			HIGH CURRENT HYBRID DRAWER CONNECTOR
WEIGHT	-			
CUSTOMER DRAWING				
SIZE	A3	QAGE CODE	00779	DRAWING NO
				292353
SCALE	NTS	SHEET	1 OF 1	REV
				A