	T D	т п	U	0 0		
4	Z M M M M M M M M M M M M M M M M M M M	ØF			4	
ယ				LAYOUT SHOWN AS EXAMPLE	3	
		Keying Shown as example				
	CHARACTERISTICS	Connector dimension	7			
	-Standard : Based on MIL-DTL-38999 Series III	DimNominalF22.25 Max				
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	Z 31.5 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any non-confor due to a use of the Products which does not the Specifications issued by either of the Parties (professional recommendation, technica	t comply with or by a third party	
N	-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			CountryJurisdiction & Control ListFRNot Listed		
				PN: 8D113F04PA		
	-Temperature Range _: -65°C to +200°C -Salt Spray : 48 hours		A 27-09-2016	A 27-09-2016 First Release		
			ISS DATE Designed By:	Latest modification - by Date:	MOD N°	
				TITLE Aluminium Inline plug 8D series		
	BASIC SERIES: 8D 1 - 13 F	04 P A	SCALE -	General linear Tolerances:	NPRDS / PROJECT	
<u> </u>	SHELL TYPE : In line Receptacle CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings)				859 1 This document is the property of	
				SOURIAU WWW.SOURIAU.COM it must not be r communicated wit		
	PLATING : F = Nickel	CONTACT LAY	YOUT : 13-04 FORMAT	SOURIAU DRG N		
			A3	8D113F04PA-C	1/2	
	H I G I	F I E	D	C B	I A	

	т	۵	п	m		0
		Contact Layout				
4	×	$ \begin{array}{c} $				
	Conta position A B C D Shell Arrangement N size no. c 13 -4	+.000 (0.00) +.150 (3.81) +.146 (3.71) +.035 (0.89) +.000 (0.00) 083 (2.11) 146 (3.71) +.035 (0.89)				
ى ى						
						SOURIAU shall no due to a use o the Specifications i (professio
N						Р
					ISS DATE Designed By:	6 First Release Latest modification Date:
<u> </u>					SCALE NA	
					FORMAT A3	WWW.
	Н	G	F	E	D	С

